PRODUCT RANGE SPECIFICATION

B65230 – Single-Station Motorised Boot Scrubber



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	B65230{PSS}	13 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b65230-boot-scrubber-motorised-single-station#specifications

01 Product description and specification

Product description

A durable boot-cleaning station that helps staff remove dirt from soles and lower sides before entering production areas. Brushing, water and soap work together in one simple routine, with straightforward controls and adjustable soap dosing to suit your cleaning process.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B65230. Grade 304 stainless steel single-user boot scrubber for one boot at a time; sole and lower side brushing; robust bristles and protective grid; manual on/off operation; 0.37kW motor with built-in motor starter protection; ½″ solenoid water control; adjustable inline peristaltic soap dosing; isolator, emergency stop and power/running pilot lights; 1½″ BSP drainage outlet at the bottom rear of the trough. Electrical options: 220V single-phase or 380V three-phase.

02 Configuration options

Electrical supply	220 V single-phase; 380 V three-phase

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 Sole and Lower Side Brushing
A single station cleans the sole and lower sides of one boot at a time. One user operates the machine at a time.

02 Hard-Wearing Bristles and Protective Grid
Robust bristles provide hard-wearing brushing, with a protective grid fitted over the brushing area.

03 Manual On/Off Operation
Switching the unit on starts brush rotation, activates water spray onto the brushes and starts inline soap dosing together.

04 Adjustable Peristaltic Soap Dosing
A peristaltic pump introduces soap into the water line. Its adjustable flow rate allows the soap feed to be set for the cleaning process.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

05 **½″ Solenoid Water Control**
The ½″ solenoid provides automatic water control during operation, supplying spray to the brushes when the unit is switched on.

06 **0.37kW Motor with Starter Protection**
A 0.37kW motor drives the brushes. A built-in motor starter provides motor protection.

07 **Isolator, Emergency Stop and Pilot Lights**
An isolator and emergency stop are provided. Separate pilot lights indicate that power is available and that the unit is running.

08 **1½″ BSP Rear Drainage Outlet**
The trough drains through a 1½″ BSP outlet positioned at its bottom rear, providing a defined drainage connection.

04 Application information

Intended applications	Footwear Cleaning and Disinfection
Industries	Dairy & Beverage Processing, Fish & Seafood Processing, Food & Beverage Processing, Fresh Produce & Packhouses, Meat & Poultry Processing

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

How does the boot scrubber operate?
The unit uses manual on/off operation. Switching it on starts the brushes rotating, activates water spray onto the brushes and starts the peristaltic soap dosing pump together.

How many people and boots can use it at once?
The B65230 is a single-user station for one boot at a time. Clean one boot, then the other.

Which parts of the boot are brushed?
The brush arrangement cleans the sole and lower sides of the boot. Robust, hard-wearing bristles and a protective grid are provided.

Which electrical configurations are available?
Choose 220V single-phase or 380V three-phase to match the required machine supply. Both configurations have a 0.37kW brush motor. Confirm the installation supply against the electrical information and nameplate supplied with the machine.

How is soap added, and can the dosing rate be adjusted?
An inline peristaltic soap dosing pump feeds soap into the water line. The pump flow rate is adjustable. Set the soap feed for the selected cleaning chemical and site cleaning procedure.

How is water supplied to the brushes?
A ½″ solenoid controls the water automatically during operation. When the unit is switched on, water activates and sprays onto the brushes.

Where is the drainage connection?
A 1½″ BSP drainage outlet is fitted at the bottom rear of the trough.

Which controls and motor protection are included?
The unit includes manual on/off controls, an isolator, an emergency stop and pilot lights for power and unit-running status. Motor protection is provided by a built-in motor starter.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357