

MODEL SPECIFICATION

B65250 – A High-Performance and Space-Saving Solution for Maintaining Optimal Hygiene in Sensitive Environments Such as Food Processing Facilities and Abattoirs. This Single-User, Walk-Through Design Processes 15-25 Users per Minute, Ensuring Efficient Boot Sanitation. Crafted from Food-Safe, Stainless Steel Grade 304, the Unit Features a Solid Frame Construction, Stainless Steel Steps, and Adjustable Feet for Stability and Durability. Standard Features • Walk-Through Design: Single-User Platform for Quick and Efficient Boot Cleaning. • High Throughput: Processes 15-25 Users per Minute, Reducing Wait Times. • Material: Stainless Steel Grade 304 (Food-Safe), Solid Frame Construction, and Steps. • Configuration: 3-Brush System (Sole & Side Scrubbing) • Soap Dosing: Inline Venturi System (Chemical Application). • Electrical Supply: 220 V Single-Phase. • Safety: Emergency Cut-Off Switch. • Water Flow: Solenoid Activated, 3/4" Inlet Valve. • Drainage: Threaded Outlet Valve, Sloped Basin. • Adjustable Feet: Four Stainless Steel Grade 304 Feet for Enhanced Stability. • Cleaning: Removable Grid. • Protection: Concealed Electrical Box.



PRODUCT IMAGE

B65250{PSS}		PRODUCT SPECIFICATION SHEET	
DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	B65250{PSS}	Published catalogue data	4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT
Electrical Supply Option	220 V single-phase	—

02 Model and supply data

Parent product	B65250 – Compact Automatic Walk-Through Boot Scrubber
Typical lead time	15 working days
Warranty	12 months

03 Specification notes

Configuration description	Walk-through motorised boot scrubber for cleaning footwear as personnel pass through a dedicated entry station. This single-user, walk-through design processes 15–25 users per minute, ensuring efficient boot sanitation. Construction and features • Walk-through design: Single-user platform for quick and efficient boot cleaning. • High throughput: Processes 15–25 users per minute, reducing wait times. • Configuration: 3-brush system (sole & side scrubbing). • Soap dosing: Inline venturi system (chemical application). • Electrical supply: 220 V single-phase. • Water flow: Solenoid activated, 3/4" inlet valve. • Drainage: Threaded outlet valve, sloped basin. • Adjustable feet: Four stainless steel Grade 304 feet for enhanced stability. • Cleaning: Removable grid. • Protection: Concealed electrical box.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield B65250. Walk Through Boot Scrubbers. Electrical supply: 220 V single-phase. Water flow: Solenoid activated, 3/4" inlet valve.
Detailed specification	• Model: B65250 • Electrical supply: 220 V single-phase • Water flow: Solenoid activated, 3/4" inlet valve • Drainage: Threaded outlet valve, sloped basin • Adjustable feet: Four stainless steel Grade 304 feet for enhanced stability • Cleaning: Removable grid

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.