

PRODUCT RANGE SPECIFICATION

B80109 – Straight Stainless Steel Grab Rail



PRODUCT IMAGE · Representative straight grab rail; choose 500 mm or 750 mm rail length.

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B80109{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

26 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

<https://basterfield.co.za/products/b80109-straight-stainless-steel-grab-rail#specifications>



01 Product description and specification

Product description

Straight general-purpose grab rail in Grade 304 stainless steel with a 32 mm diameter rail and mounting plates at both ends. Choose a 500 mm or 750 mm rail length for a wall-mounted handhold in washrooms, bathrooms and care facilities. Select the rail position and suitable wall fixings for the installation. The supplied image represents the range; the selected model determines the rail length.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B80109 straight general-purpose grab rail, Grade 304 stainless steel, 32 mm rail diameter, with mounting plates at both ends. Specify B80109(500), 500 mm rail length, or B80109(750), 750 mm rail length. Confirm wall construction, fixings, mounting position and clearances for the installation.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Diameter	32	mm	—
Mounting Type	Wall Mounted	—	—

03 Configuration options

Rail length

500 mm; 750 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01	Grade 304 stainless steel Rail manufactured from Grade 304 stainless steel.
02	32 mm rail diameter A 32 mm diameter tubular rail provides the handhold.
03	500 mm or 750 mm length Select B80109(500) for 500 mm or B80109(750) for 750 mm.
04	Mounting plates at both ends End mounting plates provide fixing points for attachment to a suitable supporting wall.
05	Straight handhold A straight central rail with returned ends, as shown in the representative product image.

05 Application information

Intended applications	Patient Care & Examination, Public Restrooms, Restrooms & Ablutions
Industries	Aged Care & Nursing Homes, Colleges & Universities, Government & Public Sector, Hospitals & Clinics, Hotels & Lodges, Schools

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.