

PRODUCT RANGE SPECIFICATION

B80113 – Dog Leg Grab Rail
Stainless Steel Grade 304



PRODUCT IMAGE · B80113 three-flange dog-leg grab rail, 300 × 300 × 300 mm.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B80113{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

21 Sep 2026

01 Product description and specification

Product description

The B80113 dog-leg grab rail is manufactured from Grade 304 stainless steel for wall-mounted support in washroom installations. Its three connected 300 mm sections form the dog-leg profile shown in the product image.

The rail has a 34 mm outside diameter and three mounting flanges with mounting plates. The overall stated dimensions are 300 × 300 × 300 mm.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B80113. Dog-leg grab rail in Grade 304 stainless steel; Ø34 mm rail; three flanges; 300 × 300 × 300 mm; supplied with mounting plates.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	300	mm	The length of the item typically as measured from left to right.
Width	300	mm	The width of the item typically as measured from front to back.
Height	300	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Diameter	34	mm	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Mounting Type	Wall Mounted	—	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B80113	Grade 304 stainless steel three-flange dog-leg grab rail, Ø34 mm, 300 × 300 × 300 mm, with mounting plates.	Overall dimensions: 300 × 300 × 300 mm (L × W × H)

04 Functional features

01	Three-flange dog-leg form Three mounting flanges support the dog-leg rail profile shown in the product image.
02	Grade 304 stainless steel The grab rail is manufactured from Grade 304 stainless steel.
03	34 mm rail diameter The tubular grab rail has a stated outside diameter of 34 mm.
04	300 × 300 × 300 mm The three stated dimensions are 300 mm × 300 mm × 300 mm.
05	Mounting plates The three wall-mounting flanges are supplied with mounting plates.

05 Application information

Intended applications	Patient Care & Examination, Public Restrooms, Restrooms & Ablutions
Industries	Aged Care & Nursing Homes, Government & Public Sector, Hospitals & Clinics

06 Supply and support

Typical lead time	5–10 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.