
PRODUCT RANGE SPECIFICATION

B80113 – Dog Leg Grab Rail Stainless Steel Grade 304



PRODUCT IMAGE · B80113 three-flange dog-leg grab rail, 300 × 300 × 300 mm.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	**B80113{PSS}**	**Published catalogue data**	**1 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b80113-dog-leg-grab-rail-stainless-steel-grade-304#specifications

01 Product description and specification

Product description

Three-flange dog-leg grab rail manufactured from Grade 304 stainless steel. The Ø34 mm rail measures 300 × 300 × 300 mm and is supplied with mounting plates.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield B80113. Dog-leg grab rail in Grade 304 stainless steel; Ø34 mm rail; three flanges; 300 × 300 × 300 mm; supplied with mounting plates.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	300	mm	The length of the item typically as measured from left to right.
Width	300	mm	The width of the item typically as measured from front to back.
Height	300	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Diameter	34	mm	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Mounting Type	Wall Mounted	–	–

03 Functional features

01 Three-flange dog-leg form
Three mounting flanges support the dog-leg rail profile shown in the product image.

02 Grade 304 stainless steel
The grab rail is manufactured from Grade 304 stainless steel.

03 34 mm rail diameter
The tubular grab rail has a stated outside diameter of 34 mm.

04 300 × 300 × 300 mm
The three stated dimensions are 300 mm × 300 mm × 300 mm.

05 Mounting plates
The three wall-mounting flanges are supplied with mounting plates.

04 Application information

Intended applications	Patient Care & Examination, Public Restrooms, Restrooms & Ablutions
Industries	Aged Care & Nursing Homes, Government & Public Sector, Hospitals & Clinics

05 Supply and support

Typical lead time	5–10 working days
Warranty	12 months

06 Frequently asked questions

What are the rail dimensions?
The stated dimensions are 300 mm × 300 mm × 300 mm.

What is the rail diameter?
The tubular grab rail has a stated outside diameter of 34 mm.

What material is used?
The grab rail is manufactured from Grade 304 stainless steel.

How many mounting flanges are provided?
The dog-leg grab rail has three mounting flanges with mounting plates.

What lead time applies?
The standard grab-rail lead time is 5–10 working days.

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.