
PRODUCT RANGE SPECIFICATION

B80114 – 45° Dog-Leg Grab Rail, Grade 304 Stainless Steel



PRODUCT IMAGE · B80114(300x300), 45° Dog-Leg Grab Rail.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**B80114{PSS}**	**20 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/b80114-45-degree-dog-leg-grab-rail#specifications

01 Product description and specification

Product description

The B80114 is a 45° dog-leg grab rail manufactured from Grade 304 stainless steel. It has a 34mm outside diameter, two 300mm leg lengths and three wall-mounting flanges. Select wall fixings to suit the mounting surface.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

B80114(300x300): 45° Dog-Leg Grab Rail; Grade 304 Stainless Steel; Ø34mm Outside Diameter; 300mm × 300mm Leg Lengths; Three Wall-Mounting Flanges.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Mounting Type	Wall Mounted	–	–
Dog-Leg Angle	45°	–	Angle of the dog-leg grab rail.
First Leg Length	300	mm	Length of one leg of the dog-leg grab rail.
Second Leg Length	300	mm	Length of one leg of the dog-leg grab rail.
Rail Outside Diameter	34	mm	Outside diameter of the tubular rail.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

03 Functional features

01 45° Dog-Leg Angle
A 45° dog-leg grab rail with two 300mm leg lengths.

02 Grade 304 Stainless Steel
Manufactured from Grade 304 stainless steel.

03 Ø34mm Outside Diameter
The tubular rail has a 34mm outside diameter.

04 Three Mounting Flanges
Three flanges provide the wall-mounting points.

04 Application information

Intended applications	Patient Care & Examination, Public Restrooms, Restrooms & Ablutions
Industries	Aged Care & Nursing Homes, Government & Public Sector, Hospitals & Clinics

05 Supply and support

Typical lead time	5–10 working days
Warranty	12 months

06 Frequently asked questions

What is the dog-leg angle?
The B80114 dog-leg angle is 45°.

What are the leg lengths?
The two stated leg lengths are 300mm × 300mm.

What material and rail diameter are used?
Grade 304 stainless steel with a 34mm outside diameter.

How is the rail mounted?
The rail has three wall-mounting flanges. Select fixings to suit the mounting surface.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357