

PRODUCT RANGE SPECIFICATION

B80120 – Hinged Fold-Down Grab Rail with Toilet Roll Holder



PRODUCT IMAGE · B80120(850) hinged fold-down grab rail with mounting plate and toilet-roll holder.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B80120{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

21 Sep 2026

01 Product description and specification

Product description

The B80120 hinged grab rail folds down from its wall-mounted position to provide support alongside a toilet. It is manufactured from Grade 304 stainless steel and has a stated rail length of 850 mm.

The assembly includes a rectangular wall-mounting plate and an integrated toilet-roll holder, as shown in the product image.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B80120(850). Fold-down hinged grab rail in Grade 304 stainless steel; 850 mm length; wall mounting plate; integrated toilet-roll holder.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	850	mm	The length of the item typically as measured from left to right.
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Mounting Type	Wall Mounted	—	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B80120(850)	Hinged fold-down grab rail in Grade 304 stainless steel, 850 mm long, with wall-mounting plate and integrated toilet-roll holder.	Overall dimensions: 850 × — × — mm (L × W × H)

04 Functional features

01 Fold-down hinged rail

The rail folds down from its wall-mounted position for use alongside a toilet.

- 02

Grade 304 stainless steel

The grab rail is manufactured from Grade 304 stainless steel.
- 03

850 mm length

The stated grab-rail length is 850 mm.
- 04

Wall-mounting plate

The hinged assembly includes a rectangular wall-mounting plate.
- 05

Toilet-roll holder

An integrated toilet-roll holder is included beneath the rail.

05 Application information

Intended applications	Patient Care & Examination, Public Restrooms, Restrooms & Ablutions
Industries	Aged Care & Nursing Homes, Government & Public Sector, Hospitals & Clinics

06 Supply and support

Typical lead time	5–10 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.