

PRODUCT RANGE SPECIFICATION

B80138 – Cistern and Flush Valve Back Grab Rail



PRODUCT IMAGE · B80138(112–750) back grab rail for cistern and flush–valve toilet installations.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

B80138{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

21 Sep 2026

01 Product description and specification

Product description

The B80138 cistern and flush valve back grab rail provides wall-mounted support behind a toilet. It is manufactured in South Africa from Grade 304 stainless steel and uses 32 mm diameter tubing.

The rail is 750 mm long and projects 216 mm from the wall. Its 75 mm diameter mounting plate has three 8 mm fixing holes. The supplied specification sheet states compliance with SANS 10400-S:2011.

Fixings such as screws and anchors are not included. Select suitable fixings for the wall material, supporting structure and installation conditions.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield B80138(112–750). Cistern and flush valve back grab rail; Grade 304 stainless steel; 32 mm rail diameter; 750 mm length; 216 mm wall projection; 75 mm mounting plate with three 8 mm holes. Fixings excluded.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	750	mm	The length of the item typically as measured from left to right.
Diameter	32	mm	—
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Mounting Type	Wall Mounted	—	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
B80138(112-750)	Cistern and flush valve back grab rail in Grade 304 stainless steel, 750 mm long with a 32 mm rail diameter and 216 mm wall projection. Fixings are not included.	Overall dimensions: 750 × – × – mm (L × W × H)

04 Functional features

01	Cistern and flush-valve layout Back grab rail designed for toilet installations using a cistern or flush valve.
02	Grade 304 stainless steel Manufactured from Grade 304 stainless steel for corrosion and stain resistance.
03	750 mm support rail The 32 mm diameter rail is 750 mm long and projects 216 mm from the wall.
04	Wall-mounted plate The 75 mm diameter mounting plate includes three 8 mm fixing holes.
05	Accessible toilet support Provides rear support for transfers and movement at accessible toilet installations.
06	South African manufacture Manufactured in South Africa.

05 Application information

Intended applications	Patient Care & Examination, Public Restrooms, Restrooms & Ablutions
Industries	Aged Care & Nursing Homes, Government & Public Sector, Hospitals & Clinics

06 Supply and support

Typical lead time	5–10 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.