MODEL SPECIFICATION

E22126(DC-112-1500) – Sink Double Centre Bowl 1500mm Length



PRODUCT IMAGE · 1500mm Double Centre Bowl Preparation Sink

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E22126(DC-112-1500){PSS}	15 Nov 2026

01 Model specification

Double Bowl Preparation Sink, Stainless Steel Grade 304, 1.2mm Thickness, 1500mm (L) × 650mm (W) × 900mm Working Height, with Two Centrally Positioned Bowls, Each 500mm (L) × 500mm (W) × 250mm (D), 150mm High Rear Splashback, Full Stainless Steel Underframe with Tubular Legs, and Adjustable Feet for Levelling

Height Specification: 900mm Working Height, with a 150mm Splashback (1050mm Overall).

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Length	1500	mm	The length of the item typically as measured from left to right.
Width	650	mm	The width of the item typically as measured from front to back.
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.
Bowl Width	500	mm	–
Bowl Depth	250	mm	–

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Bowl Orientation	Centre	—	—
Number of Bowls	2	—	—
Adjustable Feet	Yes	—	—
Leg Material	Stainless Steel	—	—
Leg Profile	Tubular	—	Tubular Stainless Steel Supporting Legs.
Undershelf	No undershelf	—	Undershelf specification for the selected table product. Grade 304 or 430; solid in 0.9 or 1.2 mm, other constructions in 1.2 mm only. Tubular uses formed open-section sheet metal.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1500	mm
Width	650	mm
Overall height	1050	mm
Weight	37	kg

04 Model and supply data

Parent product	E22126(DC-112) — Double Bowl Preparation Sinks
Typical lead time	10–15 working days
Warranty	24 months

05 Specification notes

Configuration description

Preparation Sink with Two Centrally Positioned Bowls and a Full Stainless Steel Underframe. Manufactured from 1.2mm Thick Grade 304 Stainless Steel. Plan Dimensions: 1500mm (L) × 650mm (W). Working Height: 900mm. Rear Splashback: 150mm High. Overall Height Including Splashback: 1050mm. Each Bowl: 500mm (L) × 500mm (W) × 250mm (D). Stainless Steel Tubular Legs with Adjustable Feet for Levelling.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Double Centre Bowl Preparation Sink; Grade 304 Stainless Steel, 1.2mm Thickness; 1500mm (L) × 650mm (W); 900mm Working Height; 1050mm Overall Height; Two Bowls, Each 500mm (L) × 500mm (W) × 250mm (D); 150mm Rear Splashback; Full Stainless Steel Underframe with Tubular Legs and Adjustable Feet

Detailed specification

Sink Type: Double Bowl Preparation Sink
Bowl Position: Double Centre
Material: Stainless Steel Grade 304
Material Thickness: 1.2mm
Length: 1500mm
Width: 650mm
Working Height: 900mm
Overall Height Including Splashback: 1050mm
Number of Bowls: 2
Each Bowl Length: 500mm
Each Bowl Width: 500mm
Each Bowl Depth: 250mm
Rear Splashback Height: 150mm
Underframe: Full Stainless Steel
Legs: Stainless Steel Tubular
Feet: Adjustable for Levelling
Weight: 36.546kg

06 Frequently asked questions

What are the overall dimensions?

Standard models are 650 mm wide, in lengths of 1200, 1500, 1850, 2200 and 2400 mm. An 1800 x 750 mm configuration with a solid Grade 304 stainless steel undershelf is available under advanced customisation. Working height is 900 mm; overall height is 1050 mm including the 150 mm rear splashback.

What are the bowl dimensions and orientation?

There are two centrally positioned bowls, each measuring 500 mm long x 500 mm wide x 250 mm deep.

What material is used?

The sink uses 1.2 mm thick Grade 304 stainless steel and has a full stainless steel underframe.

Which lengths are available?

Standard 650 mm wide models are available in 1200, 1500, 1850, 2200 and 2400 mm lengths. The advanced 750 mm wide configuration is 1800 mm long and includes a solid 1.2 mm Grade 304 stainless steel undershelf.

Does the 1800 x 750 mm configuration include an undershelf?

Yes. E22126(DC-112-1800x0750-S112) includes a solid undershelf made from 1.2 mm thick Grade 304 stainless steel. Enable advanced customisation to select the 750 mm width.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357