MODEL SPECIFICATION

E22126(DC-112-1200) – Prep Sink Double Centre SS304 1.2mm 1200mm



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E22126(DC-112-1200){PSS}	15 Nov 2026

01 Model specification

Preparation Sink with Two Centrally Positioned Bowls, Manufactured from 1.2 mm Thick Grade 304 Stainless Steel, with a Full Stainless Steel Underframe. Overall Plan Dimensions Are 1200 mm L x 650 mm W. The Working Height Is 900 mm; the 150 mm High Rear Splashback Brings the Overall Height to 1050 mm. Each Bowl Measures 500 mm L x 500 mm W x 250 mm D.

Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Length	1200	mm	The length of the item typically as measured from left to right.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Width	650	mm	The width of the item typically as measured from front to back.
Number of Bowls	2	–	–
Bowl Orientation	Centre	–	–
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.
Bowl Width	500	mm	–
Bowl Depth	250	mm	–
Undershelf	No undershelf	–	Undershelf specification for the selected table product. Grade 304 or 430; solid in 0.9 or 1.2 mm, other constructions in 1.2 mm only. Tubular uses formed open-section sheet metal.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1200	mm
Width	650	mm
Overall height	1050	mm

04 Model and supply data

Parent product	E22126(DC-112) — Double Bowl Preparation Sinks
Typical lead time	10–15 working days
Warranty	24 months

05 Specification notes

Configuration description

Preparation sink with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Overall plan dimensions are 1200 mm L x 650 mm W. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D.

Overall height: 1050 mm.

Short Form Specification

> **SPECIFICATION USE**
> Use this description when specifying this model.

E22126(DC-112-1200): Preparation sink with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Overall plan dimensions are 1200 mm L x 650 mm W. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D.

Overall height: 1050 mm.

Detailed specification

- Model: E22126(DC-112-1200)
- Type: preparation sink
- Length: 1200 mm
- Width: 650 mm
- Working height: 900 mm
- Overall height including splashback: 1050 mm
- Rear splashback height: 150 mm
- Sink material: stainless steel Grade 304
- Sink material thickness: 1.2 mm
- Underframe: full stainless steel
- Bowls: two, centrally positioned
- Each bowl: 500 mm L x 500 mm W x 250 mm D

Overall height: 1050 mm.

06 Frequently asked questions

What are the overall dimensions?

Standard models are 650 mm wide, in lengths of 1200, 1500, 1850, 2200 and 2400 mm. An 1800 x 750 mm configuration with a solid Grade 304 stainless steel undershelf is available under advanced customisation. Working height is 900 mm; overall height is 1050 mm including the 150 mm rear splashback.

What are the bowl dimensions and orientation?

There are two centrally positioned bowls, each measuring 500 mm long x 500 mm wide x 250 mm deep.

What material is used?

The sink uses 1.2 mm thick Grade 304 stainless steel and has a full stainless steel underframe.

Which lengths are available?

Standard 650 mm wide models are available in 1200, 1500, 1850, 2200 and 2400 mm lengths. The advanced 750 mm wide configuration is 1800 mm long and includes a solid 1.2 mm Grade 304 stainless steel undershelf.

Does the 1800 x 750 mm configuration include an undershelf?

Yes. E22126(DC-112-1800x0750-S112) includes a solid undershelf made from 1.2 mm thick Grade 304 stainless steel. Enable advanced customisation to select the 750 mm width.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357