PRODUCT RANGE SPECIFICATION

E22126(DC-112) – Double Bowl Preparation Sinks



PRODUCT IMAGE · 1800 x 750 mm configuration with solid Grade 304 undershelf

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**E22126(DC-112){PSS}**	**15 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e22126dc-112-double-bowl-preparation-sinks#specifications

01 Product description and specification

Product description

Double-centre-bowl preparation sinks in 1.2 mm Grade 304 stainless steel. Standard width 650 mm; an advanced 1800 x 750 mm configuration includes a solid stainless steel undershelf.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Grade 304 stainless steel double-centre-bowl preparation sink, 1.2 mm thick, with full stainless steel underframe. Standard width 650 mm; lengths 1200, 1500, 1850, 2200 or 2400 mm. Advanced configuration: 1800 x 750 mm with solid 1.2 mm Grade 304 undershelf. Working height 900 mm; overall height 1050 mm including 150 mm rear splashback. Two bowls, each 500 x 500 x 250 mm.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Bowl Depth	250	mm	–
Bowl Width	500	mm	–
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.

03 Configuration options

Length	1200 mm; 1500 mm; 1850 mm; 2200 mm; 2400 mm
Undershelf	No undershelf; Solid Grade 304 1.2 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 **Hygienic stainless steel construction**
Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.

02 **Designed for commercial environments**
Built for repeated daily use rather than light domestic applications.

03 **Stainless Steel Grade 304 construction, including framework**
Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.

04 **Heavy-duty fabricated construction**
Provides greater rigidity and durability under demanding commercial use.

05 **Two centre bowls**
Two centrally positioned bowls, each 500 mm L x 500 mm W x 250 mm D.

06 **Grade 304 stainless steel**
The sink is manufactured from 1.2 mm thick Grade 304 stainless steel.

07 **Full stainless steel underframe**
The sink is supported by a full stainless steel underframe.

08 **150 mm rear splashback**
The 150 mm high rear splashback brings the overall height to 1050 mm above the floor.

09 **Five standard lengths**
Standard 650 mm wide models are available in 1200, 1500, 1850, 2200 and 2400 mm lengths. An additional 1800 x 750 mm configuration with a solid undershelf is available under advanced customisation.

05 Application information

Intended applications	Food Preparation Workstations, Kitchen Washing & Warewashing
Industries	Food & Beverage Processing, Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

07 Frequently asked questions

What are the overall dimensions?

Standard models are 650 mm wide, in lengths of 1200, 1500, 1850, 2200 and 2400 mm. An 1800 x 750 mm configuration with a solid Grade 304 stainless steel undershelf is available under advanced customisation. Working height is 900 mm; overall height is 1050 mm including the 150 mm rear splashback.

What are the bowl dimensions and orientation?

There are two centrally positioned bowls, each measuring 500 mm long x 500 mm wide x 250 mm deep.

What material is used?

The sink uses 1.2 mm thick Grade 304 stainless steel and has a full stainless steel underframe.

Which lengths are available?

Standard 650 mm wide models are available in 1200, 1500, 1850, 2200 and 2400 mm lengths. The advanced 750 mm wide configuration is 1800 mm long and includes a solid 1.2 mm Grade 304 stainless steel undershelf.

Does the 1800 x 750 mm configuration include an undershelf?

Yes. E22126(DC-112-1800x0750-S112) includes a solid undershelf made from 1.2 mm thick Grade 304 stainless steel. Enable advanced customisation to select the 750 mm width.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357