

PRODUCT RANGE SPECIFICATION

E22126(DC-112) – Double Bowl Preparation Sinks



PRODUCT IMAGE · 1800 x 750 mm configuration with solid Grade 304 undershelf

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E22126(DC-112){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

5 Oct 2026

01 Product description and specification

Product description

Preparation sinks with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Standard 650 mm wide models are available in lengths of 1200, 1500, 1850, 2200 and 2400 mm. An additional 1800 x 750 mm configuration includes a solid undershelf in 1.2 mm Grade 304 stainless steel; the 750 mm width is available under advanced customisation.

Working height is 900 mm. The 150 mm rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D. Select the required configuration to view its matching item and specification sheet.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Grade 304 stainless steel double-centre-bowl preparation sink, 1.2 mm thick, with full stainless steel underframe. Standard width 650 mm; lengths 1200, 1500, 1850, 2200 or 2400 mm. Advanced configuration: 1800 x 750 mm with solid 1.2 mm Grade 304 undershelf. Working height 900 mm; overall height 1050 mm including 150 mm rear splashback. Two bowls, each 500 x 500 x 250 mm.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Bowl Depth	250	mm	—
Bowl Width	500	mm	—
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(DC-112-1200)	Preparation Sink with Two Centrally Positioned Bowls, Manufactured from 1.2 mm Thick Grade 304 Stainless Steel, with a Full Stainless Steel Underframe. Overall Plan Dimensions Are 1200 mm L x 650 mm W. The Working Height Is 900 mm; the 150 mm High Rear Splashback Brings the Overall Height to 1050 mm. Each Bowl Measures 500 mm L x 500 mm W x 250 mm D. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Width: 650 mm Overall dimensions: 1200 x 650 x 1050 mm (L x W x H)
E22126(DC-112-1500)	Preparation Sink with Two Centrally Positioned Bowls, Manufactured from 1.2 mm Thick Grade 304 Stainless Steel, with a Full Stainless Steel Underframe. Overall Plan Dimensions Are 1500 mm L x 650 mm W. The Working Height Is 900 mm; the 150 mm High Rear Splashback Brings the Overall Height to 1050 mm. Each Bowl Measures 500 mm L x 500 mm W x 250 mm D. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Width: 650 mm Overall dimensions: 1500 x 650 x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(DC-112-1800x0750-S112)	Heavy Duty Work Table with Two Centrally Positioned Bowls and a Solid Undershelf. The Worktop and Undershelf Are Manufactured from 1.2 mm Thick Grade 304 Stainless Steel. Dimensions Are 1800 mm L x 750 mm W, with a 900 mm Working Height and a 150 mm Rear Splashback (1050 mm Overall Height). Each Bowl Measures 500 mm L x 500 mm W x 250 mm D. Full Stainless Steel Underframe. The 750 mm Width Is an Advanced Customisation. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1800 mm Width: 750 mm Overall dimensions: 1800 x 750 x 1050 mm (L x W x H) Mass: 56 kg
E22126(DC-112-1850)	Preparation Sink with Two Centrally Positioned Bowls, Manufactured from 1.2 mm Thick Grade 304 Stainless Steel, with a Full Stainless Steel Underframe. Overall Plan Dimensions Are 1850 mm L x 650 mm W. The Working Height Is 900 mm; the 150 mm High Rear Splashback Brings the Overall Height to 1050 mm. Each Bowl Measures 500 mm L x 500 mm W x 250 mm D. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1850 mm Width: 650 mm Overall dimensions: 1850 x 650 x 1050 mm (L x W x H)
E22126(DC-112-2200)	Preparation Sink with Two Centrally Positioned Bowls, Manufactured from 1.2 mm Thick Grade 304 Stainless Steel, with a Full Stainless Steel Underframe. Overall Plan Dimensions Are 2200 mm L x 650 mm W. The Working Height Is 900 mm; the 150 mm High Rear Splashback Brings the Overall Height to 1050 mm. Each Bowl Measures 500 mm L x 500 mm W x 250 mm D. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2200 mm Width: 650 mm Overall dimensions: 2200 x 650 x 1050 mm (L x W x H)
E22126(DC-112-2400)	Preparation Sink with Two Centrally Positioned Bowls, Manufactured from 1.2 mm Thick Grade 304 Stainless Steel, with a Full Stainless Steel Underframe. Overall Plan Dimensions Are 2400 mm L x 650 mm W. The Working Height Is 900 mm; the 150 mm High Rear Splashback Brings the Overall Height to 1050 mm. Each Bowl Measures 500 mm L x 500 mm W x 250 mm D. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2400 mm Width: 650 mm Overall dimensions: 2400 x 650 x 1050 mm (L x W x H)

04 Functional features

01	Hygienic stainless steel construction Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.
02	Designed for commercial environments Built for repeated daily use rather than light domestic applications.
03	Stainless Steel Grade 304 construction, including framework Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.
04	Heavy-duty fabricated construction Provides greater rigidity and durability under demanding commercial use.
05	Two centre bowls Two centrally positioned bowls, each 500 mm L x 500 mm W x 250 mm D.
06	Grade 304 stainless steel The sink is manufactured from 1.2 mm thick Grade 304 stainless steel.
07	Full stainless steel underframe The sink is supported by a full stainless steel underframe.
08	150 mm rear splashback The 150 mm high rear splashback brings the overall height to 1050 mm above the floor.
09	Five standard lengths Standard 650 mm wide models are available in 1200, 1500, 1850, 2200 and 2400 mm lengths. An additional 1800 x 750 mm configuration with a solid undershelf is available under advanced customisation.

05 Application information

Intended applications	Food Preparation Workstations, Kitchen Washing & Warewashing
Industries	Food & Beverage Processing, Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.