

PRODUCT RANGE SPECIFICATION

E22126(DC-112) – Double Bowl Preparation Sinks

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE E22126(DC-112){PSS}	DATA STATUS Published catalogue data	GENERATED ON 14 Sep 2026
---------------------------------	---	---	-----------------------------

01 Product description and specification

Product description	Preparation sinks with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Choose 1200, 1500, 1850, 2200 or 2400 mm overall length. All models are 650 mm wide. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D. Select the required length to view the matching item and its specification sheet.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. E22126(DC-112) preparation sink: 1.2 mm Grade 304 stainless steel with full stainless steel underframe. Specify 1200, 1500, 1850, 2200 or 2400 mm L x 650 mm W. Working height 900 mm; overall height 1050 mm including the 150 mm rear splashback. Two centrally positioned bowls, each 500 mm L x 500 mm W x 250 mm D.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Bowl Depth	250	mm	–
Bowl Width	500	mm	–
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(DC-112-1200)	Preparation sink with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Overall plan dimensions are 1200 mm L x 650 mm W. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D.	Length: 1200 mm Overall dimensions: 1200 x 650 x 1050 mm (L x W x H)
E22126(DC-112-1500)	Preparation sink with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Overall plan dimensions are 1500 mm L x 650 mm W. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D.	Length: 1500 mm Overall dimensions: 1500 x 650 x 1050 mm (L x W x H)
E22126(DC-112-1850)	Preparation sink with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Overall plan dimensions are 1850 mm L x 650 mm W. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D.	Length: 1850 mm Overall dimensions: 1850 x 650 x 1050 mm (L x W x H)
E22126(DC-112-2200)	Preparation sink with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Overall plan dimensions are 2200 mm L x 650 mm W. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D.	Length: 2200 mm Overall dimensions: 2200 x 650 x 1050 mm (L x W x H)
E22126(DC-112-2400)	Preparation sink with two centrally positioned bowls, manufactured from 1.2 mm thick Grade 304 stainless steel, with a full stainless steel underframe. Overall plan dimensions are 2400 mm L x 650 mm W. The working height is 900 mm; the 150 mm high rear splashback brings the overall height to 1050 mm. Each bowl measures 500 mm L x 500 mm W x 250 mm D.	Length: 2400 mm Overall dimensions: 2400 x 650 x 1050 mm (L x W x H)

04 Functional features**01 Hygienic stainless steel construction**

Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.

02 Designed for commercial environments

Built for repeated daily use rather than light domestic applications.

- 03

Stainless Steel Grade 304 construction, including framework

Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.
- 04

Heavy-duty fabricated construction

Provides greater rigidity and durability under demanding commercial use.
- 05

Two centre bowls

Two centrally positioned bowls, each 500 mm L x 500 mm W x 250 mm D.
- 06

Grade 304 stainless steel

The sink is manufactured from 1.2 mm thick Grade 304 stainless steel.
- 07

Full stainless steel underframe

The sink is supported by a full stainless steel underframe.
- 08

150 mm rear splashback

The 150 mm high rear splashback brings the overall height to 1050 mm above the floor.
- 09

Five standard lengths

Choose 1200, 1500, 1850, 2200 or 2400 mm overall length. All models have a standard width of 650 mm.

05

Application information

Intended applications	Food Preparation Workstations, Kitchen Washing & Warewashing
Industries	Food & Beverage Processing, Foodservice & Catering

06

Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.