MODEL SPECIFICATION

E22126(DC-112-1500-E0600-K01) – Prep Sink DC SS304 1.2 1500x700 E600

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E22126(DC-112-1500-E0600-K01){PSS}	14 Nov 2026

01 Model specification

Double-Centre-Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1500 mm (L) x 700 mm (W), 900 mm Working Height. Two Bowls, Each 500 mm (L) x 500 mm (W) x 250 mm Deep; 600 mm Extended Splashback, Marine Edge Top, Full Stainless Steel Framework and Adjustable Feet.

Height Specification: 900 mm Working Height, with a 600 mm Splashback (1500 mm Overall).

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	600	mm	Height of the splashback above the tabletop or working surface.
Overall height	1500	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Number of Bowls	2	–	–
Bowl Orientation	Centre	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Width	700	mm	The width of the item typically as measured from front to back.
Length	1500	mm	The length of the item typically as measured from left to right.
Bowl Width	500	mm	–

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.
Bowl Depth	250	mm	—

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1500	mm
Width	700	mm
Overall height	1500	mm

04 Model and supply data

Parent product	E22126(DC-E) — Double Bowl Preparation Sink with Extended Splashback
Typical lead time	10–15 working days
Warranty	24 months

E&OE. Specifications are subject to change without notice.