

PRODUCT RANGE SPECIFICATION

E22126(DC-E) – Double Bowl Preparation Sink with Extended Splashback



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E22126(DC-E){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

24 Oct 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.
<https://basterfield.co.za/products/e22126dc-e-double-bowl-preparation-sink-with-extended-splashback#specifications>



01 Product description and specification

Product description

The Basterfield E22126(DC-E) Double Bowl Preparation Sink with Extended Splashback is a floor-standing stainless steel sink with two 500mm x 500mm x 250mm deep bowls, marine edge top and full stainless steel framework.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Shall be Basterfield E22126(DC-E) Double Bowl Preparation Sink with Extended Splashback, manufactured from 1.2 mm thick Grade 304 stainless steel as standard, with Grade 316 stainless steel and 1.5mm material thickness options available. Unit shall be floor-standing on a full stainless steel framework with adjustable feet, standard 650mm width and 900mm working height, with overall length, width and height manufactured to suit project requirements. Sink shall include two 500mm (L) x 500mm (W) x 250mm (D) bowls, marine edge worktop, Ø40mm or Ø90mm waste outlet options, and a boxed double-skin extended splashback, 300 mm high as standard, with 400, 500 and 600 mm height options. Unit shall be supplied with optional solid, tubular or perforated stainless steel undershelf and shall be suitable for commercial kitchens, food production facilities, laboratories, healthcare and hygiene-critical industrial applications.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.
Bowl Orientation	Centre	—	—
Bowl Depth	250	mm	—

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Width	500	mm	—
Number of Bowls	2	—	—

03 Configuration options

Length	1500 mm; 1850 mm; 2000 mm; 2200 mm; 2400 mm
Splashback Height	300 mm; 400 mm; 500 mm; 600 mm

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01	Hygienic stainless steel construction Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.
02	Designed for commercial environments Built for repeated daily use rather than light domestic applications.
03	Stainless Steel Grade 304 construction, including framework Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.
04	Heavy-duty fabricated construction Provides greater rigidity and durability under demanding commercial use.
05	Marine Edge Marine edge contains liquid
06	Stainless Steel Framework Framework and legs underneath table is of an all stainless steel construction ensuring suitability for high hygiene environments.
07	Extended Splashback Able to mount tapware, soap dispensers, etc.
08	Test Title Test Desc

05 Application information

Intended applications	Pot Washing
Industries	Bakeries, Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.