

PRODUCT RANGE SPECIFICATION

E22126(SR-112) – Preparation Sink with Single Right-Hand Bowl



PRODUCT IMAGE · 1200 x 650 mm right-hand bowl preparation sink, without undershelf

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E22126(SR-112){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

Single right-hand bowl preparation sink in 1.2 mm Grade 304 stainless steel. Choose a published length of 1200 or 1500 mm, a width of 650, 700 or 750 mm, and the required undershelf. The 1500 mm length is published at 650 mm wide without an undershelf. The default configuration is 1200 mm long and 650 mm wide without an undershelf.

Working height is 900 mm to the worktop. The 150 mm integral rear splashback brings the overall height to 1050 mm. The right-hand bowl measures 500 mm long x 500 mm wide x 250 mm deep and has a 40 mm waste outlet. Stainless steel legs with adjustable feet allow the sink to be levelled on site.

Undershelf choices are no undershelf, Grade 304 stainless steel at 0.9 or 1.2 mm, or Grade 430 stainless steel at 0.9 or 1.2 mm. These choices apply to the undershelf; the sink remains 1.2 mm Grade 304 stainless steel. Other lengths within the advertised 1200–2400 mm range can be specified in a bespoke enquiry.

Working height is measured from the floor to the worktop. Overall height includes the splashback and is calculated from the selected working and splashback heights.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield E22126(SR-112) preparation sink: 1.2 mm Grade 304 stainless steel, 650, 700 or 750 mm wide, 900 mm working height and 1050 mm overall height including the 150 mm integral rear splashback. One right-hand bowl, 500 x 500 x 250 mm deep, with a 40 mm waste outlet. Stainless steel legs with adjustable feet. Published lengths: 1200 mm, with undershelf none or Grade 304/430 in 0.9/1.2 mm; 1500 mm at 650 mm wide, no undershelf. Default: 1200 x 650 mm, no undershelf. Other lengths on request.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Number of Bowls	1	—	—
Bowl Orientation	Right Hand	—	—
Bowl Length	500	mm	The length of the bowl typically as measured from left to right.
Bowl Width	500	mm	—
Bowl Depth	250	mm	—
Waste Outlet Diameter	40	mm	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(SR-112-1200)	Preparation Sink Single Bowl Right Hand, Grade 304 Stainless Steel, 1.2 mm Thick. 1200 mm (L) x 650 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm (D), with 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. No Undershelf. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershelf: No undershelf Width: 650 mm Overall dimensions: 1200 x 650 x 1050 mm (L x W x H) Mass: 29 kg

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(SR-112-1200-S109)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 650 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershef in Stainless Steel Grade 304 0.9mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: Stainless Steel Grade 304 0.9mm Thickness Width: 650 mm Overall dimensions: 1200 x 650 x 1050 mm (L x W x H)
E22126(SR-112-1200-S112)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 650 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershef in Stainless Steel Grade 304 1.2mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: Stainless Steel Grade 304 1.2mm Thickness Width: 650 mm Overall dimensions: 1200 x 650 x 1050 mm (L x W x H)
E22126(SR-112-1200-S209)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 650 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershef in Stainless Steel Grade 430 0.9mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: Stainless Steel Grade 430 0.9mm Thickness Width: 650 mm Overall dimensions: 1200 x 650 x 1050 mm (L x W x H)
E22126(SR-112-1200-S212)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 650 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershef in Stainless Steel Grade 430 1.2mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: Stainless Steel Grade 430 1.2mm Thickness Width: 650 mm Overall dimensions: 1200 x 650 x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(SR-112-1200x0700)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 700 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. No Undershelf. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershelf: No undershelf Width: 700 mm Overall dimensions: 1200 x 700 x 1050 mm (L x W x H)
E22126(SR-112-1200x0700-S109)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 700 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershelf in Stainless Steel Grade 304 0.9mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershelf: Stainless Steel Grade 304 0.9mm Thickness Width: 700 mm Overall dimensions: 1200 x 700 x 1050 mm (L x W x H)
E22126(SR-112-1200x0700-S112)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 700 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershelf in Stainless Steel Grade 304 1.2mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershelf: Stainless Steel Grade 304 1.2mm Thickness Width: 700 mm Overall dimensions: 1200 x 700 x 1050 mm (L x W x H)
E22126(SR-112-1200x0700-S209)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 700 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershelf in Stainless Steel Grade 430 0.9mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershelf: Stainless Steel Grade 430 0.9mm Thickness Width: 700 mm Overall dimensions: 1200 x 700 x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(SR-112-1200x0700-S212)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 700 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershef in Stainless Steel Grade 430 1.2mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: Stainless Steel Grade 430 1.2mm Thickness Width: 700 mm Overall dimensions: 1200 x 700 x 1050 mm (L x W x H)
E22126(SR-112-1200x0750)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 750 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. No Undershef. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: No undershef Width: 750 mm Overall dimensions: 1200 x 750 x 1050 mm (L x W x H)
E22126(SR-112-1200x0750-S109)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 750 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershef in Stainless Steel Grade 304 0.9mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: Stainless Steel Grade 304 0.9mm Thickness Width: 750 mm Overall dimensions: 1200 x 750 x 1050 mm (L x W x H)
E22126(SR-112-1200x0750-S112)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 750 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershef in Stainless Steel Grade 304 1.2mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershef: Stainless Steel Grade 304 1.2mm Thickness Width: 750 mm Overall dimensions: 1200 x 750 x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22126(SR-112-1200x0750-S209)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 750 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershell in Stainless Steel Grade 430 0.9mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershell: Stainless Steel Grade 430 0.9mm Thickness Width: 750 mm Overall dimensions: 1200 x 750 x 1050 mm (L x W x H)
E22126(SR-112-1200x0750-S212)	Single Right-Hand Bowl Preparation Sink in 1.2 mm Grade 304 Stainless Steel; 1200 mm (L) x 750 mm (W), 900 mm Working Height and 1050 mm Overall Height Including the 150 mm Integral Rear Splashback. Bowl: 500 mm (L) x 500 mm (W) x 250 mm Deep, with a 40 mm Waste Outlet. Stainless Steel Legs with Adjustable Feet. Includes an Undershell in Stainless Steel Grade 430 1.2mm Thickness. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Undershell: Stainless Steel Grade 430 1.2mm Thickness Width: 750 mm Overall dimensions: 1200 x 750 x 1050 mm (L x W x H)
E22126(SR-112-1500)	Preparation Sink with a Single Right-Hand Bowl, Manufactured from 1.2 mm Thick Grade 304 Stainless Steel. Dimensions: 1500 mm L x 650 mm W, with a 900 mm Working Height. The 150 mm Integral Rear Splashback Brings the Overall Height to 1050 mm. Bowl Dimensions: 500 mm L x 500 mm W x 250 mm D. Stainless Steel Framework and Legs with Adjustable Feet. No Undershell. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Undershell: No undershell Width: 650 mm Overall dimensions: 1500 x 650 x 1050 mm (L x W x H) Mass: 34 kg

04 Functional features

- 01 1.2 mm Grade 304 Stainless Steel**
Sink manufactured from 1.2 mm Grade 304 stainless steel.
- 02 Single Right-Hand Bowl**
A 500 x 500 x 250 mm bowl sits on the right, with a work surface to the left.
- 03 Integral Rear Splashback**
150 mm splashback formed as part of the sink top.
- 04 Working and Overall Heights**
900 mm working height to the worktop; 1050 mm overall including the splashback.

- 05

Adjustable Feet

Stainless steel legs with adjustable feet for levelling during installation.
- 06

Undershelf Configurations

The base model has no undershelf. Published 1200 mm configurations also offer Grade 304 or Grade 430 undershelves in 0.9 or 1.2 mm material.

05 Application information

Intended applications	Food Preparation Workstations, Kitchen Washing & Warewashing
Industries	Food & Beverage Processing, Hotels & Lodges, Institutional & Contract Catering, Research Laboratories, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.