

MODEL SPECIFICATION

E22128(DC-112-1700-S212) – The Basterfield E22128(DC-112) Double Bowl Pot Sink with Centre Bowls is a heavy-duty stainless steel sink for hygiene-sensitive environments. Constructed from 1.2mm thick Grade 304 stainless steel, it features two 600mm x 500mm x 300mm bowls, a marine edge perimeter, integral splashback, and adjustable feet. Available in lengths from 1650mm to 2400mm, the sink includes Ø40mm waste outlets and a 60mm tapware landing. Optional undershelves or tubular racks provide additional storage flexibility. Length: 1700. Undershelf: Stainless Steel Grade 430 1.2mm Thickness.



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	E22128(DC-112-1700-S212) {PSS}	Published catalogue data	14 Sep 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	1700	mm	The length of the item typically as measured from left to right.
Undershelf	Stainless Steel Grade 430 1.2mm Thickness	—	Choose the undershelf or rack option for this sink. The available options specify the construction, material and thickness where applicable.

02 Model and supply data

Parent product	E22128(DC-112) – Double Bowl Pot Sink with Centre Bowls
Typical lead time	10–15 working days
Warranty	12 months

Configuration description	Double-bowl pot sink with centrally positioned bowls for washing cookware in commercial and institutional kitchens. Selected configuration: Length: 1700 mm; Undershelf: stainless steel Grade 430 1.2 mm Thickness.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield E22128(DC-112-1700-S212). Double-bowl pot sink with centrally positioned bowls for washing cookware in commercial and institutional kitchens. Selected configuration: Length: 1700 mm; Undershelf: stainless steel Grade 430 1.2 mm Thickness.
Detailed specification	• Model: E22128(DC-112-1700-S212) • Length: 1700 mm • Undershelf: stainless steel Grade 430 1.2 mm Thickness

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.