MODEL SPECIFICATION

E22128(DC-112-1500x700-S112) – Double Centre Pot Sink 1500x700 SS304 1.2 S112

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E22128(DC-112-1500x700-S112){PSS}	19 Nov 2026

01 Model specification

Double-Centre-Bowl Pot Sink in 1.2 mm Grade 304 Stainless Steel. 1500 mm L x 700 mm W; 900 mm Working Height with a 150 mm Rear Splashback (1050 mm Overall). Two Bowls, Each 600 mm L x 500 mm W x 300 mm D, with Pre-Punched 40 mm Diameter Holes. Marine Edge, Stainless Steel Underframe and Framework, and Adjustable Feet. Undershelf: Stainless Steel Grade 304 1.2mm Thickness. 700 mm Width Is an Advanced Customisation; Price Confirmed by Quotation.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Number of Bowls	2	–	–
Bowl Orientation	Centre	–	–
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The thickness of the material used for the item's primary construction. The thickness of individual components may vary.
Width	700	mm	The width of the item typically as measured from front to back.
Bowl Length	600	mm	The length of the bowl typically as measured from left to right.
Bowl Depth	300	mm	–

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Width	500	mm	—
Length	1500	mm	The length of the item typically as measured from left to right.
Undershelf	Stainless Steel Grade 304 1.2mm Thickness	—	Choose the undershelf or rack option for this sink. The available options specify the construction, material and thickness where applicable.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Length	1500	mm
Width	700	mm
Overall height	1050	mm

04 Model and supply data

Parent product	E22128(DC-112) — Grade 304 Double Bowl Centre Pot Sink
Typical lead time	10–15 working days
Warranty	24 months

05 Specification notes

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Double-centre-bowl pot sink in 1.2 mm Grade 304 stainless steel. 1500 mm L x 700 mm W; 900 mm working height with a 150 mm rear splashback (1050 mm overall). Two bowls, each 600 mm L x 500 mm W x 300 mm D, with pre-punched 40 mm diameter holes. Marine edge, stainless steel underframe and framework, and adjustable feet. Undershelf: Stainless Steel Grade 304 1.2mm Thickness. 700 mm width is an advanced customisation; price confirmed by quotation.

Detailed specification

- Model: E22128(DC-112-1500x700-S112)
- Length: 1500 mm
- Width: 700 mm (advanced customisation)
- Working height: 900 mm
- Overall height: 1050 mm
- Rear splashback: 150 mm
- Sink material: stainless steel Grade 304
- Sink material thickness: 1.2 mm
- Edge: marine edge
- Bowls: two, centrally positioned
- Each bowl: 600 mm L x 500 mm W x 300 mm D
- Waste outlets: 40 mm diameter holes, pre-punched in each bowl
- Underframe and framework: stainless steel
- Feet: adjustable
- Undershelf: Stainless Steel Grade 304 1.2mm Thickness
- Price: on request

06 Frequently asked questions

Which lengths are available?

Choose 1500, 1650, 1700, 1800, 1850, 2200 or 2400 mm. The standard width is 650 mm. A 700 mm width is available through advanced customisation; pricing is confirmed by quotation.

What are the bowl dimensions?

There are two centrally positioned bowls. Each bowl measures 600 mm long x 500 mm wide x 300 mm deep and has a pre-punched waste outlet hole (see the selected model for size).

What is the difference between working height and overall height?

The working height is 900 mm. The 150 mm rear splashback brings the overall height to 1050 mm. Both dimensions should be allowed for when planning the installation.

Is an undershelf included?

All seven lengths are available without an undershelf. At 1500, 1650, 1700, 2200 and 2400 mm, you can also choose a Grade 304 or Grade 430 stainless steel undershelf in 0.9 or 1.2 mm thickness, or a stainless steel tubular rack. The 1850 x 650 mm E22128(DC-112-1850-S112) model is also available with a heavy-duty 1.2 mm Grade 304 stainless steel undershelf, fully stainless steel framework, underframe and legs, and adjustable plastic feet for easy floor levelling.

Which material is used?

The sink body is Grade 304 stainless steel at 1.2 mm thickness. The underframe and framework are stainless steel. Undershelf materials are specified separately in the selected option.

Where can I find the model specification?

Choose the required length and undershelf, then open the matching item specification sheet. Standard models are 650 mm wide. Enable advanced options to select a 700 mm width. The product specification sheet lists the published configurations.

E&OE. Specifications are subject to change without notice.