PRODUCT RANGE SPECIFICATION

E22128(DL) – Double Bowl Left-Hand Pot Sink



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	E22128(DL){PSS}	19 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e22128dl-double-bowl-left-hand-pot-sink#specifications

01 Product description and specification

Product description

E22128(DL) heavy-duty double bowl pot sink with two left-hand bowls and a right-hand drainer. Full Grade 304 or 316 stainless steel construction and sub frame, with no timber or galvanised backing, on stainless steel tubular legs with adjustable feet.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Shall be Basterfield E22128(DL) double bowl left-hand pot sink, manufactured from Grade 304 or Grade 316 stainless steel in 1.2 mm or 1.5 mm material thickness, comprising two 600 mm (L) x 500 mm (W) x 300 mm (D) wash bowls positioned to the left-hand side, each with a pre-punched waste outlet hole, and an integral right-hand draining board. Unit shall be available in standard lengths of 1850, 2000, 2200 and 2400 mm with a standard width of 650 mm or optional 700 mm, a working height of 900 mm and an integral 150 mm high rear splashback providing an overall height of 1050 mm. Construction shall be full stainless steel, including the sub frame and stainless steel tubular legs, with stainless steel cross-bracing and no timber, galvanised or other corrodible backing materials. Unit shall be freestanding on adjustable feet. Waste outlets are not included and shall be specified separately.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Length	600	mm	The length of the bowl typically as measured from left to right.
Bowl Orientation	Left Hand	–	–
Bowl Width	500	mm	–
Number of Bowls	2	–	–
Bowl Depth	300	mm	–

03 Configuration options

Length	1850 mm; 2000 mm; 2200 mm; 2400 mm
Material Thickness	1.2 mm; 1.5 mm
Material	Stainless Steel Grade 304; Stainless Steel Grade 316

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 **Hygienic stainless steel construction**
Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.

02 **Designed for commercial environments**
Built for repeated daily use rather than light domestic applications.

03 **Stainless Steel Grade 304 construction, including framework**
Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.

04 **Heavy-duty fabricated construction**
Provides greater rigidity and durability under demanding commercial use.

05 **Deep pot-washing bowl**
Provides the capacity required to wash large pots, pans, containers and utensils that cannot be accommodated in conventional sink bowls.

06 **Two Left-Hand Bowls**
Two 600 x 500 x 300 mm deep bowls on the left, with a draining board to the right.

07 **No Timber or Galvanised Backing**
Sink, sub frame and legs are stainless steel, with no timber, galvanised or other corrodible backing.

08 **Tubular Legs with Adjustable Feet**
Stainless steel tubular legs with adjustable feet for levelling on uneven floors.

09 **Pre-Punched Waste Outlet Holes**
Each bowl has a pre-punched waste outlet hole. Waste outlets are an optional accessory.

10 **Grade 304 or 316**
Available in Grade 304 or Grade 316 stainless steel, in 1.2 mm or 1.5 mm thickness.

05 Application information

Intended applications	Kitchen Washing & Warewashing, Pot Washing
Industries	Food & Beverage Processing, Hospitals & Clinics, Hotels & Lodges, Institutional & Contract Catering, Meat & Poultry Processing, Restaurants & Cafés, Schools

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

07 Frequently asked questions

Are waste outlets included?

No. Each bowl has a pre-punched waste outlet hole (see the selected model for size), but waste outlets are not included. The Dura 817 waste is available as an optional accessory; two are recommended, one per bowl.

What are the bowl dimensions?

Each of the two bowls is 600 mm long, 500 mm wide and 300 mm deep.

Is there any timber or galvanised steel in the unit?

No. The sink, sub frame and legs are all stainless steel. No timber, galvanised or other corrodible backing material is used.

Which lengths are available?

Standard lengths are 1850, 2000, 2200 and 2400 mm. The standard width is 650 mm, with a 700 mm option.

What is the difference between working height and overall height?

The working height is 900 mm. The 150 mm rear splashback brings the overall height to 1050 mm.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357