

PRODUCT RANGE SPECIFICATION

E22128(SC) – Single Bowl Centre Pot Sink

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE E22128(SC){PSS}	DATA STATUS Published catalogue data	GENERATED ON 19 Sep 2026
---------------------------------	---------------------------------------	---	-----------------------------

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bowl Length	600	mm	The length of the bowl typically as measured from left to right.
Bowl Orientation	Centre	–	–
Bowl Width	500	mm	–
Number of Bowls	1	–	–
Bowl Depth	300	mm	–
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22128(SC-112-0900)	Pot Sink Single Bowl to E22128{PSS} Stainless Steel Grade 304 1.2 mm Thickness 900 mm L x 650 mm W x 900 mm H Bowl Dimensions 600 mm x 500 mm x 300 mm with 150 mm High Splash Back to Rear, Stainless Steel Legs and Adjustable Feet	Length: 900 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Width: 650 mm
E22128(SC-112-0950)	Single Bowl Centre Pot Sink 950mm SS304 1.2	Length: 950 mm Material: Stainless Steel Grade 304 Material Thickness: 1.2 mm Width: 650 mm

03 Functional features

01	Hygienic stainless steel construction Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.
02	Designed for commercial environments Built for repeated daily use rather than light domestic applications.
03	Stainless Steel Grade 304 construction, including framework Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.
04	Heavy-duty fabricated construction Provides greater rigidity and durability under demanding commercial use.

05 Deep pot-washing bowl

Provides the capacity required to wash large pots, pans, containers and utensils that cannot be accommodated in conventional sink bowls.

04 Application information

Intended applications	Pot Washing
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.