

PRODUCT RANGE SPECIFICATION

E22128(SL-112) – Grade 304 Single Bowl Left-Hand Pot Sink

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	E22128(SL-112){PSS}	Published catalogue data	19 Sep 2026

01 Product description and specification

Product description	Pot sink with a single left-hand bowl for washing cookware in commercial and institutional kitchens. Featuring a left-hand deep bowl (500 mm width x 600 mm length x 300 mm depth), this unit is suited to washing large cookware, making it a perfect fit for restaurants, catering operations, and food production facilities. Durable stainless steel Construction • A fully welded stainless steel frame with reinforced legs enhances durability and structural integrity. Optimized for Commercial Use • 150 mm high rear splashback helps prevent water splashes, keeping work areas clean and sanitary. • Integrated 40 mm waste outlet provides efficient drainage for fast and effective cleaning. • Adjustable stainless steel feet allow easy levelling on uneven floors. Size Options & Customization • Standard length: 1600 mm (custom sizes available on request). • Standard width: 650 mm (alternative widths: 600 mm or 700 mm available). • Tabletop height: 900 mm (1050 mm including splashback). This left-hand bowl pot sink is part of a versatile range that includes right-hand and centre bowl configurations, offering flexibility for different workspace layouts. Need Custom Dimensions? Working height is measured from the floor to the worktop. Overall height includes the splashback and is calculated from the selected working and splashback heights.
---------------------	---

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield E22128(SL-112). Pot Sink Single Left Hand Bowl. Material: stainless steel Grade 304. Material Thickness: 1.2 mm. Length: 1200 mm, 1600 mm. Number of Bowls: 1. 150 mm high rear splashback helps prevent water splashes, keeping work areas clean and sanitary. Integrated 40 mm waste outlet provides efficient drainage for fast and effective cleaning.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	Floor to the tabletop or working surface; excludes any splashback.
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Bowl Length	600	mm	The length of the bowl typically as measured from left to right.
Bowl Width	500	mm	—
Bowl Depth	300	mm	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22128(SL-112-1200)	Height specification: 900 mm working height, with a 150 mm splashback (1050 mm overall).	Length: 1200 mm Overall dimensions: — × — × 1050 mm (L × W × H)
E22128(SL-112-1600)	Pot Sink 1600mm Length Single Bowl Left Hand Stainless Steel Grade 304 1.2mm Thickness Height specification: 900 mm working height, with a 150 mm splashback (1050 mm overall).	Length: 1600 mm Overall dimensions: — × — × 1050 mm (L × W × H)

04 Functional features

01	Hygienic stainless steel construction Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.
02	Designed for commercial environments Built for repeated daily use rather than light domestic applications.
03	Stainless Steel Grade 304 construction, including framework Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.
04	Heavy-duty fabricated construction Provides greater rigidity and durability under demanding commercial use.
05	Deep pot-washing bowl Provides the capacity required to wash large pots, pans, containers and utensils that cannot be accommodated in conventional sink bowls.

05 Application information

Intended applications	Pot Washing
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.