

PRODUCT RANGE SPECIFICATION

E22128(TC) – Triple Bowl Centre Pot Sink

DOCUMENT SCOPE Product range	DOCUMENT REFERENCE E22128(TC){PSS}	DATA STATUS Published catalogue data	GENERATED ON 19 Sep 2026
---------------------------------	---------------------------------------	---	-----------------------------

01 Product description and specification

Product description	Triple bowl pot sink in Grade 304 stainless steel for commercial and institutional cookware washing areas. Choose the overall length and material thickness. The 2250 mm model has three custom bowls, each 600 mm long x 400 mm wide x 400 mm deep. This model is available in either 1.2 mm or 1.5 mm stainless steel thickness. The 2800 mm model has three bowls, each 600 mm long x 500 mm wide x 300 mm deep, with draining boards to each side. The 2800 mm model is available in 1.5 mm thickness only. Both lengths are 650 mm wide and have a 150 mm rear splashback, stainless steel framework and legs with adjustable feet. Select a configuration to view its exact bowl dimensions and specification sheet.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. E22128(TC) triple bowl pot sink in Grade 304 stainless steel, 650 mm wide, with a 150 mm rear splashback, stainless steel framework and adjustable feet. 2250 mm length: three custom 600 x 400 x 400 mm deep bowls; 1.2 or 1.5 mm thickness. 2800 mm length: three 600 x 500 x 300 mm deep bowls and draining boards to each side; 1.5 mm thickness only. Specify length and thickness.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Bowl Width	500	mm	—
Width	650	mm	The width of the item typically as measured from front to back.
Bowl Depth	300	mm	—
Number of Bowls	3	—	—
Bowl Orientation	Centre	—	—
Bowl Length	600	mm	The length of the bowl typically as measured from left to right.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Splashback Height	150	mm	Height of the splashback above the tabletop or working surface.

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E22128(TC-112-2250x650-C0100)	Triple bowl pot sink in 1.2 mm Grade 304 stainless steel, 2250 mm long x 650 mm wide. Three bowls, each 600 mm (L) x 400 mm (W) x 400 mm deep. 150 mm rear splashback, stainless steel framework and legs with adjustable feet. The 2250 mm model uses the specified custom bowls.	Length: 2250 mm Material Thickness: 1.2 mm Overall dimensions: 2250 x 650 x – mm (L x W x H)
E22128(TC-115-2250-C0100)	Triple bowl pot sink in 1.5 mm Grade 304 stainless steel, 2250 mm long x 650 mm wide. Three bowls, each 600 mm (L) x 400 mm (W) x 400 mm deep. 150 mm rear splashback, stainless steel framework and legs with adjustable feet. The 2250 mm model uses the specified custom bowls.	Length: 2250 mm Material Thickness: 1.5 mm Overall dimensions: 2250 x 650 x – mm (L x W x H)
E22128(TC-115-2800)	Triple bowl pot sink in 1.5 mm Grade 304 stainless steel, 2800 mm long x 650 mm wide. Three bowls, each 600 mm (L) x 500 mm (W) x 300 mm deep. 150 mm rear splashback, stainless steel framework and legs with adjustable feet. Draining boards to each side. The 2800 mm model requires 1.5 mm thickness.	Length: 2800 mm Material Thickness: 1.5 mm Overall dimensions: 2800 x 650 x – mm (L x W x H)

04 Functional features

01	Hygienic stainless steel construction Smooth, non-porous surfaces are easy to clean and suitable for commercial hygiene environments.
02	Designed for commercial environments Built for repeated daily use rather than light domestic applications.
03	Stainless Steel Grade 304 construction, including framework Provides excellent corrosion resistance, durability and hygiene in normal commercial kitchen and food-service environments.
04	Heavy-duty fabricated construction Provides greater rigidity and durability under demanding commercial use.
05	Deep pot-washing bowl Provides the capacity required to wash large pots, pans, containers and utensils that cannot be accommodated in conventional sink bowls.

05 Application information

Intended applications	Pot Washing
Industries	Food & Beverage Processing, Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.