MODEL SPECIFICATION

E23100003L – Bain-Marie Countertop 3 Division L3 3kW

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E23100003L{PSS}	14 Nov 2026

01 Model specification

Countertop Bain-Marie, Stainless Steel, 3kW, 3 Divisions, with Variable Heat Control, Drain Tap, 1.2m Flexible Cord and Three-Pin Plug, L3 Model with Low-Water-Level Protection; Inserts and Lids Supplied Separately; Basterfield E23100003L(PSS)

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Bain-Marie Model	3 Divisions L3	–	–
Material	Stainless Steel	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

03 Model and supply data

Parent product	E23100 — Electric Countertop Bain-Marie
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The E23100 is a stainless steel countertop bain-marie for buffet and serving areas. Select a one-, two- or three-division model, or the three-division L3 model with low-water-level protection.

The range uses 3 kW immersion heating with variable heat control. A drain tap, 1.2 m flexible cord and three-pin plug are fitted. Low-water-level protection is specified for the L3 model.

Insert containers and lids are supplied separately. The selected model has its own existing item code, so the division count and L3 option are recorded on the quote.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield E23100003L; stainless steel countertop bain-marie; 3 divisions; 3 kW immersion heating; variable heat control; drain tap; 1.2 m flexible cord and three-pin plug; L3 model with low-water-level protection; inserts and lids supplied separately.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Detailed specification	• Model: E23100003L • Divisions: 3 • Material: Stainless steel • Heating power: 3 kW • Control: Variable heat control • Drain tap: Fitted • Flexible cord: 1.2 m • Plug: Three pin • L3 model: Low-water-level protection • Insert containers and lids: Supplied separately

05 Frequently asked questions

Which models can I select?

Choose 1 Division, 2 Divisions, 3 Divisions or 3 Divisions L3. The selected model has its own item code.

Which model includes low-water-level protection?

Low-water-level protection is specified for the three-division L3 model, E23100003L.

Are insert containers and lids included?

No. Insert containers and lids are supplied separately and should be specified with the quotation.

What heating and drainage features are specified?

The range has 3 kW immersion heating with variable heat control, a drain tap, a 1.2 m flexible cord and a three-pin plug.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357