MODEL SPECIFICATION

E24111(SL3015) – Urn Electric SL3 3kW 15L Low-Water Protection



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E24111(SL3015){PSS}	14 Nov 2026

01 Model specification

Electric Water Urn SL3, Grade 304 Stainless Steel, 3kW, 15L, with Simmerstat Control, Low-Water-Level Protection, Refill Warning Light, Draw-Off Tap with Replaceable Seat, Insulated Handles, 1.2m Cord and Three-Pin Plug, Basterfield E24111(SL3015)

02 Technical specifications

PARAMETER	VALUE	UNIT
Capacity	15	L

03 Model and supply data

Parent product	E24111(SL3) — SL3 Electric Water Urn with Low-Water-Level Protection
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The E24111(SL3015) is the 15L configuration of the SL3 3 kW electric water urn in Grade 304 stainless steel.

The urn has simmerstat heat control and a protection system that disconnects the element at a preset low water level. A warning light indicates that refilling is needed. A draw-off tap with replaceable seat, insulated carrying handles, 1.2 m flexible cord and three-pin plug are fitted.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield E24111(SL3015) SL3 electric water urn; Grade 304 stainless steel; 3 kW; 15L; simmerstat heat control; low-water-level protection and refill warning light; draw-off tap with replaceable seat; insulated carrying handles; 1.2 m flexible cord and three-pin plug.

Detailed specification

- Model: E24111(SL3015)
- Range: SL3
- Product type: Electric water urn
- Material: Grade 304 stainless steel
- Heating power: 3 kW
- Capacity: 15 L
- Heat control: Simmerstat
- Low-water-level protection: Element disconnection at preset low level
- Warning light: Indicates refilling is needed
- Draw-off tap: Replaceable seat
- Handles: Insulated carrying handles
- Flexible cord length: 1.2 m
- Plug: Three pin

05 Frequently asked questions

Is low-water-level protection included?

Yes. Low-water-level protection is part of the E24111(SL3) range. It disconnects the element at a preset low water level.

What does the warning light indicate?

The warning light indicates that the water level is low and refilling is needed.

Which capacities are available?

The published SL3 configurations are 8 L, 10 L, 12 L, 15 L, 20 L, 25 L, 30 L, 40 L, 50 L and 75 L. Select the capacity to identify the required item code.

What controls and fittings are standard?

The range includes simmerstat heat control, a draw-off tap with replaceable seat, insulated carrying handles, a 1.2 m flexible cord and a three-pin plug.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357