PRODUCT RANGE SPECIFICATION

E24111(SL3) – SL3 Electric Water Urn with Low-Water-Level Protection



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	E24111(SL3){PSS}	14 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e24111sl3-sl3-electric-water-urn-with-low-water-level-protection#specifications

01 Product description and specification

Product description	Grade 304 stainless steel SL3 electric water urn with 3 kW heating, simmerstat control and low-water-level protection; select 8–75 L capacity.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this product range. Basterfield E24111(SL3) electric water urn; Grade 304 stainless steel; 3 kW; simmerstat heat control; low-water-level element disconnection and refill warning light; draw-off tap with replaceable seat; insulated carrying handles; 1.2 m flexible cord and three-pin plug. Published capacity 8, 10, 12, 15, 20, 25, 30, 40, 50 or 75 L as selected.

02 Configuration options

Capacity	10 choices, from 8 L to 75 L

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 Low-Water-Level Protection
The protection system disconnects the element at a preset low water level, with a warning light indicating that refilling is needed.

02 Ten Published Capacities
Choose 8 L, 10 L, 12 L, 15 L, 20 L, 25 L, 30 L, 40 L, 50 L or 75 L; the listed models use 3 kW heating.

03 Simmerstat Heat Control
Simmerstat control is fitted for the SL3 urn heating system.

04 Standard Dispensing and Handling Fittings
A draw-off tap with replaceable seat, insulated carrying handles, 1.2 m flexible cord and three-pin plug are fitted.

04 Application information

Intended applications	Hot Water and Beverage Service

04 Application information

Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

Is low-water-level protection included?

Yes. Low-water-level protection is part of the E24111(SL3) range. It disconnects the element at a preset low water level.

What does the warning light indicate?

The warning light indicates that the water level is low and refilling is needed.

Which capacities are available?

The published SL3 configurations are 8 L, 10 L, 12 L, 15 L, 20 L, 25 L, 30 L, 40 L, 50 L and 75 L. Select the capacity to identify the required item code.

What controls and fittings are standard?

The range includes simmerstat heat control, a draw-off tap with replaceable seat, insulated carrying handles, a 1.2 m flexible cord and a three-pin plug.

E&OE. Specifications are subject to change without notice.