

PRODUCT RANGE SPECIFICATION

E24111(SL3) – SL3 Electric Water Urn with Low-Water-Level Protection



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E24111(SL3){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

The E24111(SL3) electric water urn combines simmerstat heat control with low-water-level protection for catering beverage service. The protection system disconnects the element at a preset low water level, and a warning light indicates that refilling is needed.

Grade 304 stainless steel construction includes a draw-off tap with replaceable seat and insulated carrying handles. A 1.2 m flexible cord and three-pin plug are fitted. Select the required capacity from the published configurations.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield E24111(SL3). Grade 304 stainless steel electric water urn; simmerstat control; low-water-level protection and warning light; draw-off tap; insulated handles; 1.2 m cord and three-pin plug. Capacity as selected.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E24111(SL3008)	Urn Electric Type SL3 3KW with Low Water Level Protection System) 8L	Capacity: 8 L
E24111(SL3010)	Urn Electric Type SL3 3KW with Low Water Level Protection System 10L	Capacity: 10 L
E24111(SL3012)	Urn Electric Type SL3 3KW with Low Water Level Protection System 12L	Capacity: 12 L
E24111(SL3015)	Urn Electric Type SL3 3KW with Low Water Level Protection System 15L	Capacity: 15 L
E24111(SL3020)	Urn Electric Type SL3 3KW with Low Water Level Protection System 20L	Capacity: 20 L
E24111(SL3025)	Urn Electric Type SL3 3KW with Low Water Level Protection System 25L	Capacity: 25 L
E24111(SL3030)	Urn Electric Type SL3 3KW with Low Water Level Protection System 30L	Capacity: 30 L
E24111(SL3040)	Urn Electric Type SL3 3KW with Low Water Level Protection System 40L	Capacity: 40 L

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E24111(SL3050)	Urn Electric Type SL3 3KW with Low Water Level Protection System 50L	Capacity: 50 L
E24111(SL3075)	Urn Electric Type SL3 3KW with Low Water Level Protection System 75L	Capacity: 75 L

03 Application information

Intended applications	Hot Water and Beverage Service
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.