

MODEL SPECIFICATION

E24111TL3015 – URN ELECTRIC  
TYPE TL3 3KW WITH LOW WATER  
LEVEL PROTECTION SYSTEM TO  
E24111TL3015 15L



PRODUCT IMAGE

DOCUMENT SCOPE  
Model

DOCUMENT REFERENCE  
E24111TL3015{PSS}

DATA STATUS  
Published catalogue data

GENERATED ON  
14 Sep 2026

01 Technical specifications

| PARAMETER | VALUE | UNIT |
|-----------|-------|------|
| Capacity  | 15    | l    |

02 Model and supply data

|                   |                                                                               |
|-------------------|-------------------------------------------------------------------------------|
| Parent product    | E24111(TL3) – TL3 Electric Water Urn with Thermostat and Low-Level Protection |
| Typical lead time | 10–15 working days                                                            |
| Warranty          | 12 months                                                                     |

03 Specification notes

|                           |                                                                                                                                                                                                                                                                                    |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Configuration description | <p>Electric hot water urn with thermostatic control and low-level protection for catering and food service settings.</p> <p>Selected configuration: Capacity: 15 L.</p>                                                                                                            |
| Short Form Specification  | <p><b>SPECIFICATION USE</b></p> <p>Use this description when specifying this model.</p> <p>Basterfield E24111TL3015. Electric hot water urn with thermostatic control and low-level protection for catering and food service settings. Selected configuration: Capacity: 15 L.</p> |
| Detailed specification    | <ul style="list-style-type: none"><li>• Model: E24111TL3015</li><li>• Capacity: 15 L</li></ul>                                                                                                                                                                                     |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.