MODEL SPECIFICATION

E24111TL3010 – Urn Electric Type TL3 3KW with Low Water Level Pro



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E24111TL3010{PSS}	14 Nov 2026

01 Model specification

Urn Electric Type TL3 3KW with Low Water Level Protection System to E24111TL3010 10L

02 Technical specifications

PARAMETER	VALUE	UNIT
Capacity	10	L

03 Model and supply data

Parent product	E24111(TL3) — TL3 Electric Water Urn with Thermostat and Low-Level Protection
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

Electric hot water urn with thermostatic control and low-level protection for catering and food service settings.

Selected configuration: Capacity: 10 L.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this model.

Basterfield E24111TL3010. Electric hot water urn with thermostatic control and low-level protection for catering and food service settings. Selected configuration: Capacity: 10 L.

Detailed specification

- Model: E24111TL3010
- Capacity: 10 L

05 Frequently asked questions

What does the low-water-level system do?

At the preset low water level, the system cuts electrical supply to the heating element and illuminates a warning light to indicate that the urn needs refilling.

How can I check the water level?

Use the sight glass to check the water level. The low-level warning light indicates that the urn needs refilling when the preset low level is reached.

Which capacities can I select?

The published capacity choices are 8, 10, 12, 15, 20, 25, 30, 40, 50 and 75 L. Choose the required capacity in the configurator and quote the exact selected item code.

What electrical information should I confirm when ordering?

Confirm the electrical rating and installation supply requirements for the exact selected item. The E24111(TL3030) 30 L model has a 3 kW power rating; confirm the rating separately when selecting another model.

E&OE. Specifications are subject to change without notice.