MODEL SPECIFICATION

E24488(T9250) – Boiler Water Electric Thermostatic 9kW 250L



PRODUCT IMAGE

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E24488(T9250){PSS}	14 Nov 2026

01 Model specification

Water Boiler Electric, Stainless Steel, 9kW, 250L, with Adjustable Thermostat, Mechanical Filling, Level Control, Guarded Sight Glass, Power and Ready Indicators, and Dispensing Taps; Basterfield Model E24488(T9250)

02 Technical specifications

PARAMETER	VALUE	UNIT
Capacity	250	L

03 Model and supply data

Parent product	E24488(T9) — 9 kW Thermostatic Water Boiler
Typical lead time	10–15 working days
Warranty	12 months

04 Specification notes

Configuration description

The E24488(T9250) is the 250L configuration of the E24488(T9) 9 kW thermostatic electric water boiler.

Mechanical filling, level control and a guarded sight glass are fitted as standard. A power indicator shows when electrical power is present, and a ready-to-dispense indicator shows when the set water temperature has been reached. Positive-action, non-drip dispensing taps are designed for cleaning, and the stainless steel construction provides access to components for service.

Optional extras include mild steel or stainless steel wall-mounting brackets, a 1/2-inch or 1-inch ball drain valve, and a low-water-level protection system. Specify required extras with the selected capacity; low-water-level protection is an option on this range.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

Short Form Specification	**SPECIFICATION USE** Use this description when specifying this model. Basterfield E24488(T9250) stainless steel electric water boiler; 9 kW; 250L; adjustable thermostat; mechanical filling and level control; guarded sight glass; power and ready indicators; dispensing taps. Wall brackets, drain valve and low-water-level protection optional.
Detailed specification	• Model: E24488(T9250) • Product type: Electric thermostatic water boiler • Material: Stainless steel • Heating power: 9 kW • Capacity: 250 L • Control: Adjustable thermostat • Filling: Mechanical • Level control: Standard • Sight glass: Guarded • Indicators: Power and ready to dispense • Dispensing taps: Standard • Optional extras: Wall brackets, ball drain valve and low-water-level protection

05 Frequently asked questions

Which capacities are available?

The published range includes 75 L, 90 L, 100 L, 150 L, 200 L and 250 L models. Each uses 9 kW heating.

Is low-water-level protection standard?

No. A low-water-level protection system is an optional extra on the E24488(T9) range and must be specified when required.

What is fitted as standard?

Standard fittings include an adjustable thermostat, mechanical filling, level control, a guarded sight glass, power and ready-to-dispense indicators, and dispensing taps.

Which mounting and drainage options can I specify?

Optional extras include mild steel or stainless steel wall-mounting brackets and a 1/2-inch or 1-inch ball drain valve. Confirm the required arrangement with the selected capacity.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357