

PRODUCT RANGE SPECIFICATION

E24488(T9) – 9 kW Thermostatic Water Boiler



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E24488(T9){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

9 kW thermostatic water boiler with mechanical filling, level control and a guarded sight glass for commercial catering and hot water dispensing.

Stainless steel construction and well thought out design combine to ensure that the water boiler is easy to clean and maintain. Exclusive design provides easy access to components for quick service and cleaning.

Construction and features

- Power signal light to indicate electrical power to the water boiler.
- Ready-to-dispense signal light indicating that the correct water temperature has been reached.
- An easily adjustable, quality thermostat.
- Positive action, easily cleaned, non-drip taps.
- Mechanical filling, level control and a sight glass complete with guard are fitted as standard.

Optional extras

- Mild steel or stainless steel wall mounting brackets.
- 1/2" or 1" ball valve drain valve.
- Low water level protection system.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield E24488(T9). 9 kW Thermostatic Water Boiler. Capacity: 75 L, 90 L, 100 L, 150 L, 200 L, 250 L. An easily adjustable, quality thermostat. Mechanical filling, level control and a sight glass complete with guard are fitted as standard.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E24488(T9075)	Water Boiler Electric 9KW to E24488(PSS) 75L	Capacity: 75 L
E24488(T9090)	Water Boiler Electric 9kw E24488(pss) 90l	Capacity: 90 L

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E24488(T9100)	Boiler Water Electric 9KW to E24488PSS) 100L	Capacity: 100 L
E24488(T9150)	Boiler Water Electric 9KW to E24488(PSS) 150L	Capacity: 150 L
E24488(T9200)	Boiler Water Electric 9KW to E24488(PSS) 200L	Capacity: 200 L
E24488(T9250)	Boiler Water Electric 9KW to E24488(PSS) 250L	Capacity: 250 L

03 Application information

Intended applications	Hot Water and Beverage Service
Industries	Hospitals & Clinics, Hotels & Lodges, Institutional & Contract Catering

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.