PRODUCT RANGE SPECIFICATION

E24488(T9) – 9 kW Thermostatic Water Boiler



PRODUCT IMAGE

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	E24488(T9){PSS}	14 Nov 2026

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e24488t9-9-kw-thermostatic-water-boiler#specifications

01 Product description and specification

Product description	9 kW thermostatic stainless steel water boiler in 75–250 L capacities, with mechanical filling, level control and guarded sight glass.
Short Form Specification	**SPECIFICATION USE** Use this description when specifying this product range. Basterfield E24488(T9) electric thermostatic water boiler, stainless steel, 9 kW; capacity 75, 90, 100, 150, 200 or 250 L as selected; adjustable thermostat, mechanical filling, level control, guarded sight glass, power and ready-to-dispense indicators and dispensing taps. Wall brackets, drain valve and low-water-level protection are optional extras.

02 Configuration options

Capacity	75 L; 90 L; 100 L; 150 L; 200 L; 250 L

Options vary by model; not every combination is available. Use the product page to select a model.

03 Functional features

01 Six Published Capacities
Choose 75 L, 90 L, 100 L, 150 L, 200 L or 250 L; each published model uses 9 kW heating.

02 Thermostat and Status Indicators
An adjustable thermostat is paired with power and ready-to-dispense indicators.

03 Filling and Level Visibility
Mechanical filling, level control and a sight glass with guard are fitted as standard.

04 Specify the Required Extras
Wall brackets, a ball drain valve and low-water-level protection are optional extras.

04 Application information

Intended applications	Hot Water and Beverage Service

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

04 Application information

Industries	Hospitals & Clinics, Hotels & Lodges, Institutional & Contract Catering

05 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

06 Frequently asked questions

Which capacities are available?

The published range includes 75 L, 90 L, 100 L, 150 L, 200 L and 250 L models. Each uses 9 kW heating.

Is low-water-level protection standard?

No. A low-water-level protection system is an optional extra on the E24488(T9) range and must be specified when required.

What is fitted as standard?

Standard fittings include an adjustable thermostat, mechanical filling, level control, a guarded sight glass, power and ready-to-dispense indicators, and dispensing taps.

Which mounting and drainage options can I specify?

Optional extras include mild steel or stainless steel wall-mounting brackets and a 1/2-inch or 1-inch ball drain valve. Confirm the required arrangement with the selected capacity.

E&OE. Specifications are subject to change without notice.

121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357