

MODEL SPECIFICATION

E24890S3002 – Milk Boiler Type S3
3KW to E24890S3002(PSS) 2L



PRODUCT IMAGE

DOCUMENT SCOPE
Model

DOCUMENT REFERENCE
E24890S3002{PSS}

DATA STATUS
Published catalogue data

GENERATED ON
4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT
Capacity	2	L

02 Model and supply data

Parent product	E24890(S3) – S3 Electric Milk Boiler
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	S3 electric milk boiler with a water jacket, simmerstat heat control and guarded sight glass for milk heating in dairy and catering applications. Selected configuration: Capacity: 2 L.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield E24890S3002. S3 electric milk boiler with a water jacket, simmerstat heat control and guarded sight glass for milk heating in dairy and catering applications. Selected configuration: Capacity: 2 L.
Detailed specification	• Model: E24890S3002 • Capacity: 2 L

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.