

MODEL SPECIFICATION

E24890S3025 – Milk Boiler Type S3
3KW to E24890S3025(PSS) 25L



PRODUCT IMAGE

DOCUMENT SCOPE

Model

DOCUMENT REFERENCE

E24890S3025{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT
Capacity	25	L

02 Model and supply data

Parent product	E24890(S3) – S3 Electric Milk Boiler
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	S3 electric milk boiler with a water jacket, simmerstat heat control and guarded sight glass for milk heating in dairy and catering applications. Selected configuration: Capacity: 25 L.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield E24890S3025. S3 electric milk boiler with a water jacket, simmerstat heat control and guarded sight glass for milk heating in dairy and catering applications. Selected configuration: Capacity: 25 L.
Detailed specification	• Model: E24890S3025 • Capacity: 25 L

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.