

PRODUCT RANGE SPECIFICATION

E24890(S3) – S3 Electric Milk Boiler



PRODUCT IMAGE

① Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE

Product range

DOCUMENT REFERENCE

E24890(S3){PSS}

DATA STATUS

Published catalogue data

GENERATED ON

4 Oct 2026

01 Product description and specification

Product description

The E24890(S3) electric milk boiler uses a water jacket to heat milk for dairy preparation and catering service. A simmerstat switch provides variable heat control, while a guarded sight glass shows the jacket water level.

Separate draw-off taps provide access to milk and jacket water. Insulated carrying handles, a 1.2 m flexible cord and a three-pin plug are fitted.

Select the required milk capacity from the published configurations. Follow the supplied operating instructions for filling, heating and cleaning.

Short Form Specification

SPECIFICATION USE

Use this description when specifying this product range.

Basterfield E24890(S3). Electric milk boiler with water jacket; simmerstat heat control; guarded water-level sight glass; draw-off taps; insulated handles; 1.2 m cord and three-pin plug. Milk capacity as selected.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E24890(S3005)	Milk Boiler Without Low Level Protection 5l	Capacity: 5 L
E24890S3002	Milk Boiler Type S3 3KW to E24890S3002(PSS) 2L	Capacity: 2 L
E24890S3010	Milk Boiler Type S3 3KW to E24890S3010(PSS) 10L	Capacity: 10 L
E24890S3015	Milk Boiler Type S3 3KW to E24890S3015(PSS) 15L	Capacity: 15 L
E24890S3020	Milk Boiler Type S3 3KW to E24890S3020(PSS) 20L	Capacity: 20 L
E24890S3025	Milk Boiler Type S3 3KW to E24890S3025(PSS) 25L	Capacity: 25 L
E24890S3030	Milk Boiler Type S3 3KW to E24890S3030(PSS) 30L	Capacity: 30 L

Intended applications	Hot Water and Beverage Service
Industries	Dairy & Beverage Processing, Hotels & Lodges, Institutional & Contract Catering

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.