

MODEL SPECIFICATION

E24890SL3002 – Milk Boiler Type
SL3 3KW with Low Water Level
Protection System to
E24890SL3002(PSS) 2L



PRODUCT IMAGE

DOCUMENT SCOPE

Model

DOCUMENT REFERENCE

E24890SL3002{PSS}

DATA STATUS

Published catalogue data

GENERATED ON

5 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT
Capacity	2	L

02 Model and supply data

Parent product	E24890(SL3) – SL3 Electric Milk Boiler with Low-Level Protection
Typical lead time	10–15 working days
Warranty	12 months

03 Specification notes

Configuration description	SL3 electric milk boiler with a water jacket, simmerstat control and low-level protection for milk heating in dairy and catering applications. Selected configuration: Capacity: 2 L.
Short Form Specification	SPECIFICATION USE Use this description when specifying this model. Basterfield E24890SL3002. SL3 electric milk boiler with a water jacket, simmerstat control and low-level protection for milk heating in dairy and catering applications. Selected configuration: Capacity: 2 L.
Detailed specification	- Model: E24890SL3002 - Capacity: 2 L

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.