

PRODUCT RANGE SPECIFICATION

E24890(SL3) – SL3 Electric Milk Boiler with Low-Level Protection

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	E24890(SL3){PSS}	Published catalogue data	14 Sep 2026

01 Product description and specification

Product description	The E24890(SL3) electric milk boiler uses a water jacket to heat milk for dairy preparation and catering service. It combines simmerstat heat control with low-water-level protection. A guarded sight glass shows the jacket water level, and draw-off taps provide access to the contents. Insulated carrying handles, a 1.2 m flexible cord and a three-pin plug are fitted. Select the required capacity from the published configurations and follow the supplied operating instructions for filling, heating and cleaning.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Basterfield E24890(SL3). Electric milk boiler with water jacket; simmerstat control; low-water-level protection; guarded sight glass; draw-off taps; insulated handles; 1.2 m cord and three-pin plug. Capacity as selected.

02 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E24890(SL3005)	Milk Boiler Type SL3 3kw Low Water Level Prot 5L	Capacity: 5 l
E24890(SL3010)	MILK BOILER TYPE SL3 3KW WITH LOW WATER LEVEL PROTECTION SYSTEM TO E24890SL3(PSS) 10L	Capacity: 10 l
E24890(SL3015)	Milk Boiler Type SL3 3kw With Low Water Level 15L	Capacity: 15 l
E24890(SL3020)	Milk Boiler Type SL3 3kW with Low Water Level Protection System 20L Capacity	Capacity: 20 l
E24890(SL3030)	Milk Boiler Type SL3 3kw With Low Water Level Protection System To E24890(sl3){pss} 30l	Capacity: 30 l
E24890SL3002	MILK BOILER TYPE SL3 3KW WITH LOW WATER LEVEL PROTECTION SYSTEM TO E24890SL3002(PSS) 2L	Capacity: 2 l
E24890SL3025	MILK BOILER TYPE SL3 3KW WITH LOW WATER LEVEL PROTECTION SYSTEM TO E24890SL3025(PSS) 25L	Capacity: 25 l

Intended applications	Hot Water and Beverage Service
Industries	Dairy & Beverage Processing, Foodservice & Catering

04 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

Product drawings and images



PRODUCT IMAGE

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.