MODEL SPECIFICATION

E25144(109-0500x600-L212AR300) – Table, Slatted Shelf 500 mmx600 mm SB300 mm

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Model	E25144(109-0500x600-L212AR300) {PSS}	14 Nov 2026

01 Model specification

Grade 304 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Slatted Grade 430 1.2 mm. Stainless Steel Frame with Adjustable Feet.

Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	850	mm	The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.
Splashback Height	300	mm	The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop.
Overall height	1150	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	500	mm	The length of the item typically as measured from left to right.
Width	600	mm	The width of the item typically as measured from front to back.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Undershelf	Slatted Grade 430 1.2 mm	—	Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.
Material Thickness	0.9	mm	The worktop is Grade 304 stainless steel, 0.9 mm thick.

03 Dimensions and mass

PARAMETER	VALUE	UNIT
Overall height	1150	mm

04 Model and supply data

Parent product	E25144(109) — Grade 304 Eco Preparation Table (0.9 mm) with Rear Splashback
Typical lead time	10–15 working days
Warranty	24 months

05 Frequently asked questions

What is the standard configuration?

The standard worktop is 0.9 mm thick and the standard working height is 900 mm. The worktop is Grade 304 stainless steel. Stainless steel frame with adjustable feet.

Which undershelf options are available?

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

Which sizes are available?

Lengths: 500, 900, 1200, 1500, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Available combinations vary by undershelf and worktop specification; select the required options in the configurator.

Which advanced options are available?

Advanced customisation offers 850 mm or 1000 mm working heights. Rear splashback heights of 300 mm and 450 mm are also available.

How is the height measured?

The rear splashback is 150 mm high as standard, with 300 mm and 450 mm advanced options. Working height is measured from the floor to the worktop; overall height includes the splashback.

Can I choose another stainless steel grade?

The worktop and table range remain Grade 304; the selected undershelf specification is shown separately. Whole-table Grade 304, Grade 430 and Grade 316 tables remain separate product alternatives. Grade 316 tables are outside the Eco range.

E&OE. Specifications are subject to change without notice.