

MODEL SPECIFICATION

E25144(109-0500x0600-L212) – Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Slatted Grade 430 1.2 mm. Stainless steel frame with adjustable feet.

DOCUMENT SCOPE Model	DOCUMENT REFERENCE E25144(109-0500x0600-L212){PSS}	DATA STATUS Published catalogue data	GENERATED ON 15 Sep 2026
-------------------------	---	---	-----------------------------

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Length	500	mm	The length of the item typically as measured from left to right.
Height	900	mm	The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.
Width	600	mm	The width of the item typically as measured from front to back.
Splashback Height	150	mm	The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop.
Undershelf	Slatted Grade 430 1.2 mm	–	Supplied with a slatted undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only.
Material Thickness	0.9	mm	The worktop is Grade 304 stainless steel, 0.9 mm thick.

02 Model and supply data

Parent product	E25144(109-L) – Grade 304 Eco Preparation Table (0.9 mm) with Rear Splashback and Slatted Undershelf
----------------	--

02 Model and supply data

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.