

MODEL SPECIFICATION

**E25144(109-0500x600-L112BR300) – Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Slatted Grade 304 1.2 mm. Stainless steel frame with adjustable feet.**

|                         |                                                           |                                         |                             |
|-------------------------|-----------------------------------------------------------|-----------------------------------------|-----------------------------|
| DOCUMENT SCOPE<br>Model | DOCUMENT REFERENCE<br>E25144(109-0500x600-L112BR300){PSS} | DATA STATUS<br>Published catalogue data | GENERATED ON<br>15 Sep 2026 |
|-------------------------|-----------------------------------------------------------|-----------------------------------------|-----------------------------|

01 Technical specifications

| PARAMETER          | VALUE                     | UNIT | TECHNICAL NOTE                                                                                                                                                                                  |
|--------------------|---------------------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Height             | 1000                      | mm   | The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.                                                 |
| Material           | Stainless Steel Grade 304 | –    | The primary material used in the construction of the item. Certain components may be manufactured from different materials.                                                                     |
| Undershelf         | Slatted Grade 304 1.2 mm  | –    | Supplied with a slatted undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only.                                                                                                      |
| Length             | 500                       | mm   | The length of the item typically as measured from left to right.                                                                                                                                |
| Width              | 600                       | mm   | The width of the item typically as measured from front to back.                                                                                                                                 |
| Material Thickness | 0.9                       | mm   | The worktop is Grade 304 stainless steel, 0.9 mm thick.                                                                                                                                         |
| Splashback Height  | 300                       | mm   | The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. |

02 Model and supply data

|                |                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------|
| Parent product | E25144(109-L) – Grade 304 Eco Preparation Table (0.9 mm) with Rear Splashback and Slatted Undershelf |
|----------------|------------------------------------------------------------------------------------------------------|

02 Model and supply data

|                   |                    |
|-------------------|--------------------|
| Typical lead time | 10-15 working days |
| Warranty          | 12 months          |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.