

PRODUCT RANGE SPECIFICATION

E25144(109-T) – Grade 304 Eco Preparation Table (0.9 mm) with Rear Splashback and Tubular Undershelf

|                |                    |                          |              |
|----------------|--------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE | DATA STATUS              | GENERATED ON |
| Product range  | E25144(109-T){PSS} | Published catalogue data | 16 Sep 2026  |

01 Product description and specification

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product description | <p>Basterfield E25144(109-T). An economical preparation table for catering kitchens and foodservice work areas. Eco refers to the economical product range.</p> <p>The worktop is Grade 304 stainless steel, 0.9 mm thick. Stainless steel frame with adjustable feet. Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available.</p> <p>The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.</p> <p>Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal.</p> <p>Whole-table Grade 304, Grade 430 and Grade 316 ranges are separate product alternatives, rather than material customisations. A Grade 430 undershelf does not change the specified worktop grade.</p> |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Short Form Specification | <p><b>SPECIFICATION USE</b></p> <p>Use this description when specifying this product range.</p> <p>Shall be Basterfield E25144(109-T), a Grade 304 stainless steel preparation table with rear splashback. The worktop is Grade 304 stainless steel, 0.9 mm thick. Stainless steel frame with adjustable feet. Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights. The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal.</p> |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

02 Technical specifications

| PARAMETER          | VALUE                     | UNIT | TECHNICAL NOTE                                                                                                              |
|--------------------|---------------------------|------|-----------------------------------------------------------------------------------------------------------------------------|
| Material           | Stainless Steel Grade 304 | –    | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |
| Material Thickness | 0.9                       | mm   | The worktop is Grade 304 stainless steel, 0.9 mm thick.                                                                     |

## 02 Technical specifications

| PARAMETER                | VALUE | UNIT | TECHNICAL NOTE                                                                              |
|--------------------------|-------|------|---------------------------------------------------------------------------------------------|
| Product Range            | Eco   | —    | Product classification detail retained during the September 2026 catalogue category review. |
| Splashback Configuration | Rear  | —    | Product classification detail retained during the September 2026 catalogue category review. |

## 03 Models and configurations

| MODEL                      | DESCRIPTION                                                                                                                                                                                                                                                                                                                       | PUBLISHED CONFIGURATION                                                                                                               |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| E25144(109-0500x0600-T112) | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| E25144(109-0500x0600-T212) | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| E25144(109-0500x0650-T112) | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| E25144(109-0500x0650-T212) | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| E25144(109-0500x0700-T112) | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x700-T212)</b>      | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x600-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x600-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x600-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0500x600-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0500x600-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x600-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x600-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x600-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x600-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0500x600-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0500x600-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x600-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x600x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0500x600x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0500x600x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x600x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0500x650-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x650-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x650-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0500x650-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0500x650-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x650-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x650-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x650-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x650-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0500x650-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0500x650-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x650-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x650x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x650x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0500x650x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x650x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0500x700-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x700-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0500x700-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x700-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0500x700-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0500x700x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0500x700x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0500x700x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |

## 03 Models and configurations

| MODEL                                | DESCRIPTION                                                                                                                                                                                                                                                                                                                       | PUBLISHED CONFIGURATION                                                                                                               |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0500x700x850-T212)</b> | Grade 304 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 850 mm<br>Length: 500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0900x0600-T112)</b>    | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x0600-T212)</b>    | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x0650-T112)</b>    | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0900x0650-T212)</b>    | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0900x0700-T112)</b>    | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x0700-T212)</b>     | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x600-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x600-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x600-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x600-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x600-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x600-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x600-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x600-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x600-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x600-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x600-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x600-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x600x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x600x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-0900x600x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x600x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-0900x650-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x650-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x650-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0900x650-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0900x650-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x650-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x650-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x650-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x650-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0900x650-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0900x650-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x650-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x650x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x650x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-0900x650x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x650x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-0900x700-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x700-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0900x700-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x700-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0900x700-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 900 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-0900x700x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0900x700x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-0900x700x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |

## 03 Models and configurations

| MODEL                                | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-0900x700x850-T212)</b> | Grade 304 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 900 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x0600-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x0600-T212)</b>    | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x0650-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1200x0650-T212)</b>    | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1200x0700-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x0700-T212)</b>     | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x600-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x600-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x600-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x600-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x600-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x600-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x600-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x600-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x600-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x600-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x600-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x600-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x600x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x600x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1200x600x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x600x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1200x650-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x650-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x650-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1200x650-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1200x650-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x650-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x650-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x650-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x650-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1200x650-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1200x650-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x650-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x650x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x650x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1200x650x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x650x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1200x700-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x700-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1200x700-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x700-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1200x700-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1200 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1200x700x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1200x700x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1200x700x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |

## 03 Models and configurations

| MODEL                                | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1200x700x850-T212)</b> | Grade 304 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 850 mm<br>Length: 1200 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1500x0600-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x0600-T212)</b>    | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x0650-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1500x0650-T212)</b>    | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1500x0700-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x0700-T212)</b>     | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x600-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x600-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x600-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x600-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x600-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x600-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x600-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x600-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x600-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x600-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x600-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x600-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x600x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x600x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1500x600x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x600x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1500x650-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x650-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x650-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1500x650-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1500x650-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x650-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x650-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x650-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x650-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1500x650-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1500x650-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x650-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x650x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x650x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1500x650x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x650x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1500x700-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x700-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1500x700-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x700-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1500x700-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1500 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1500x700x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1500x700x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1500x700x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |

## 03 Models and configurations

| MODEL                                | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1500x700x850-T212)</b> | Grade 304 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 850 mm<br>Length: 1500 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1800x0600-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x0600-T212)</b>    | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x0650-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1800x0650-T212)</b>    | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1800x0700-T112)</b>    | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x0700-T212)</b>     | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x600-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x600-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x600-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x600-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x600-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x600-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x600-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x600-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x600-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x600-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x600-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x600-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x600x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x600x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-1800x600x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x600x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-1800x650-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x650-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x650-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1800x650-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1800x650-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x650-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x650-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x650-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x650-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1800x650-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1800x650-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x650-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x650x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x650x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-1800x650x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x650x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-1800x700-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x700-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1800x700-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x700-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1800x700-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 1800 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-1800x700x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1800x700x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-1800x700x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |

## 03 Models and configurations

| MODEL                                | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-1800x700x850-T212)</b> | Grade 304 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 850 mm<br>Length: 1800 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2000x0600-T112)</b>    | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x0600-T212)</b>    | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x0650-T112)</b>    | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2000x0650-T212)</b>    | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2000x0700-T112)</b>    | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x0700-T212)</b>     | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x600-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x600-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x600-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x600-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x600-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x600-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x600-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x600-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x600-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x600-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x600-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x600-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x600x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x600x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2000x600x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x600x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2000x650-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x650-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x650-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2000x650-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2000x650-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x650-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x650-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x650-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x650-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2000x650-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2000x650-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x650-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x650x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x650x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2000x650x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x650x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2000x700-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x700-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2000x700-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x700-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2000x700-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2000 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2000x700x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2000x700x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2000x700x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |

## 03 Models and configurations

| MODEL                                | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2000x700x850-T212)</b> | Grade 304 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 850 mm<br>Length: 2000 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2400x0600-T112)</b>    | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x0600-T212)</b>    | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x0650-T112)</b>    | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2400x0650-T212)</b>    | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2400x0700-T112)</b>    | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x0700-T212)</b>     | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x600-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x600-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x600-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x600-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x600-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x600-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x600-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x600-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x600-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x600-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x600-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x600-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x600x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x600x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm |
| <b>E25144(109-2400x600x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x600x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 600 mm  |
| <b>E25144(109-2400x650-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x650-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x650-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2400x650-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2400x650-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x650-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x650-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x650-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x650-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2400x650-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2400x650-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x650-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x650x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x650x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm |
| <b>E25144(109-2400x650x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x650x850-T212)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 650 mm  |
| <b>E25144(109-2400x700-T112AR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700-T112AR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700-T112BR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x700-T112BR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2400x700-T112R300)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700-T112R450)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700-T212AR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700-T212AR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700-T212BR300)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

## 03 Models and configurations

| MODEL                                 | DESCRIPTION                                                                                                                                                                                                                                                                                                                         | PUBLISHED CONFIGURATION                                                                                                                 |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>E25144(109-2400x700-T212BR450)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2400x700-T212R300)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 300 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700-T212R450)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 900 mm<br>Length: 2400 mm<br>Splashback Height: 450 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm  |
| <b>E25144(109-2400x700x1000-T112)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2400x700x1000-T212)</b> | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 1000 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |
| <b>E25144(109-2400x700x850-T112)</b>  | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 304 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal.  | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 304 1.2 mm (open section)<br>Width: 700 mm  |

03 Models and configurations

| MODEL                         | DESCRIPTION                                                                                                                                                                                                                                                                                                                        | PUBLISHED CONFIGURATION                                                                                                                |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| E25144(109-2400x700x850-T212) | Grade 304 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame with adjustable feet. Tubular undershelf uses formed open-section sheet metal. | Height: 850 mm<br>Length: 2400 mm<br>Splashback Height: 150 mm<br>Undershelf: Tubular Grade 430 1.2 mm (open section)<br>Width: 700 mm |

04 Functional features

|    |                                                                                                                                                                                                                                          |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 01 | <b>Grade 304 stainless steel worktop</b><br>The worktop is Grade 304 stainless steel, 0.9 mm thick.                                                                                                                                      |
| 02 | <b>Rear splashback height choices</b><br>The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. |
| 03 | <b>Tubular undershelf included</b><br>Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal.                                                |
| 04 | <b>Working height</b><br>The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.                                                                 |
| 05 | <b>Size choices</b><br>Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available.                                                                                                           |
| 06 | <b>Intended working areas</b><br>An economical preparation table for catering kitchens and foodservice work areas. Eco refers to the economical product range.                                                                           |

05 Application information

|                       |                                                                         |
|-----------------------|-------------------------------------------------------------------------|
| Intended applications | Food Preparation Workstations                                           |
| Industries            | Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés |

06 Supply and support

|                   |                    |
|-------------------|--------------------|
| Typical lead time | 10–15 working days |
| Warranty          | 12 months          |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.