

MODEL SPECIFICATION

**E25144(112-0500x0600-P112) – Grade 304 Stainless Steel Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 1.2 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless Steel Frame with Adjustable Feet. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).**

|                |                                 |                          |              |
|----------------|---------------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE              | DATA STATUS              | GENERATED ON |
| Model          | E25144(112-0500x0600-P112){PSS} | Published catalogue data | 5 Oct 2026   |

01 Technical specifications

| PARAMETER          | VALUE                     | UNIT | TECHNICAL NOTE                                                                                                                                                                                  |
|--------------------|---------------------------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Working Height     | 900                       | mm   | The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.                                                 |
| Splashback Height  | 150                       | mm   | The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. |
| Overall height     | 1050                      | mm   | Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.                                                                   |
| Material           | Stainless Steel Grade 304 | —    | The primary material used in the construction of the item. Certain components may be manufactured from different materials.                                                                     |
| Material Thickness | 1.2                       | mm   | The worktop is Grade 304 stainless steel, 1.2 mm thick. Advanced customisation offers 1.5 mm or 2 mm worktops.                                                                                  |
| Length             | 500                       | mm   | The length of the item typically as measured from left to right.                                                                                                                                |

01 Technical specifications

| PARAMETER  | VALUE                       | UNIT | TECHNICAL NOTE                                                                                |
|------------|-----------------------------|------|-----------------------------------------------------------------------------------------------|
| Width      | 600                         | mm   | The width of the item typically as measured from front to back.                               |
| Undershelf | Perforated Grade 304 1.2 mm | —    | Supplied with a perforated undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. |

02 Dimensions and mass

| PARAMETER      | VALUE | UNIT |
|----------------|-------|------|
| Overall height | 1050  | mm   |

03 Model and supply data

|                   |                                                                                                       |
|-------------------|-------------------------------------------------------------------------------------------------------|
| Parent product    | E25144(112-P) – Grade 304 Heavy Duty Preparation Table with Rear Splashback and Perforated Undershelf |
| Typical lead time | 10–15 working days                                                                                    |
| Warranty          | 12 months                                                                                             |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.