

MODEL SPECIFICATION

E25144(112-0500x0600-S109) – Grade 304 Stainless Steel Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 1.2 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Solid Grade 304 0.9 mm. Stainless Steel Frame with Adjustable Feet. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	E25144(112-0500x0600-S109){PSS}	Published catalogue data	7 Oct 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Working Height	900	mm	The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.
Splashback Height	150	mm	The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop.
Overall height	1050	mm	Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.
Undershelf	Solid Grade 304 0.9 mm	—	Supplied with a solid undershelf in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm.
Material	Stainless Steel Grade 304	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	The worktop is Grade 304 stainless steel, 1.2 mm thick. Advanced customisation offers 1.5 mm or 2 mm worktops.

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Length	500	mm	The length of the item typically as measured from left to right.
Width	600	mm	The width of the item typically as measured from front to back.

02 Dimensions and mass

PARAMETER	VALUE	UNIT
Overall height	1050	mm

03 Model and supply data

Parent product	E25144(112-S) – Grade 304 Heavy Duty Preparation Table with Rear Splashback and Solid Undershef
Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.