

PRODUCT RANGE SPECIFICATION

E25144(209) – Grade 430 Eco Preparation Table (0.9 mm) with Rear Splashback

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	E25144(209){PSS}	Published catalogue data	6 Oct 2026

Detailed item specifications

Select an item code for its detailed specification sheet, including model dimensions, technical specifications and drawings. For a printed copy, scan the QR code or visit the product page and select the item.

<https://basterfield.co.za/products/e25144209-grade-430-eco-preparation-table-09-mm-with-rear-splashback#specifications>



01 Product description and specification

Product description	Grade 430 Eco table with a 0.9 mm worktop, 150 mm rear splashback, without an undershelf. Advanced 300 mm and 450 mm splashback heights available.
Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Shall be Basterfield E25144(209), a Grade 430 stainless steel preparation table with rear splashback. The worktop is Grade 430 stainless steel, 0.9 mm thick. Stainless steel frame with adjustable feet. Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights. The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. Supplied without an undershelf. Select a separate solid, slatted, perforated or tubular undershelf product when storage is required.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 430	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	The worktop is Grade 430 stainless steel, 0.9 mm thick.
Undershelf	No undershelf	—	Undershelf specification for the selected table product. Grade 304 or 430; solid in 0.9 or 1.2 mm, other constructions in 1.2 mm only. Tubular uses formed open-section sheet metal.
Product Range	Eco	—	—
Splashback Configuration	Rear	—	—

03 Models and configurations

ITEM CODE	LENGTH	WIDTH	WORKING HEIGHT	REAR SPLASHBACK HEIGHT
<u>E25144(209-0500x0600)</u>	500 mm	600 mm	900 mm	150 mm
<u>E25144(209-0500x0650)</u>	500 mm	650 mm	900 mm	150 mm
<u>E25144(209-0500x0700)</u>	500 mm	700 mm	900 mm	150 mm
<u>E25144(209-0500x600-R300)</u>	500 mm	600 mm	900 mm	300 mm
<u>E25144(209-0500x600-R450)</u>	500 mm	600 mm	900 mm	450 mm
<u>E25144(209-0500x600x1000)</u>	500 mm	600 mm	1000 mm	150 mm
<u>E25144(209-0500x600x1000-R300)</u>	500 mm	600 mm	1000 mm	300 mm
<u>E25144(209-0500x600x1000-R450)</u>	500 mm	600 mm	1000 mm	450 mm
<u>E25144(209-0500x600x850)</u>	500 mm	600 mm	850 mm	150 mm
<u>E25144(209-0500x600x850-R300)</u>	500 mm	600 mm	850 mm	300 mm
<u>E25144(209-0500x600x850-R450)</u>	500 mm	600 mm	850 mm	450 mm
<u>E25144(209-0500x650-R300)</u>	500 mm	650 mm	900 mm	300 mm
<u>E25144(209-0500x650-R450)</u>	500 mm	650 mm	900 mm	450 mm
<u>E25144(209-0500x650x1000)</u>	500 mm	650 mm	1000 mm	150 mm
<u>E25144(209-0500x650x1000-R300)</u>	500 mm	650 mm	1000 mm	300 mm
<u>E25144(209-0500x650x1000-R450)</u>	500 mm	650 mm	1000 mm	450 mm
<u>E25144(209-0500x650x850)</u>	500 mm	650 mm	850 mm	150 mm
<u>E25144(209-0500x650x850-R300)</u>	500 mm	650 mm	850 mm	300 mm
<u>E25144(209-0500x650x850-R450)</u>	500 mm	650 mm	850 mm	450 mm
<u>E25144(209-0500x700-R300)</u>	500 mm	700 mm	900 mm	300 mm
<u>E25144(209-0500x700-R450)</u>	500 mm	700 mm	900 mm	450 mm
<u>E25144(209-0500x700x1000)</u>	500 mm	700 mm	1000 mm	150 mm
<u>E25144(209-0500x700x1000-R300)</u>	500 mm	700 mm	1000 mm	300 mm
<u>E25144(209-0500x700x1000-R450)</u>	500 mm	700 mm	1000 mm	450 mm
<u>E25144(209-0500x700x850)</u>	500 mm	700 mm	850 mm	150 mm
<u>E25144(209-0500x700x850-R300)</u>	500 mm	700 mm	850 mm	300 mm
<u>E25144(209-0500x700x850-R450)</u>	500 mm	700 mm	850 mm	450 mm
<u>E25144(209-0900x0600)</u>	900 mm	600 mm	900 mm	150 mm
<u>E25144(209-0900x0650)</u>	900 mm	650 mm	900 mm	150 mm
<u>E25144(209-0900x0700)</u>	900 mm	700 mm	900 mm	150 mm
<u>E25144(209-0900x600-R300)</u>	900 mm	600 mm	900 mm	300 mm
<u>E25144(209-0900x600-R450)</u>	900 mm	600 mm	900 mm	450 mm
<u>E25144(209-0900x600x1000)</u>	900 mm	600 mm	1000 mm	150 mm
<u>E25144(209-0900x600x1000-R300)</u>	900 mm	600 mm	1000 mm	300 mm
<u>E25144(209-0900x600x1000-R450)</u>	900 mm	600 mm	1000 mm	450 mm
<u>E25144(209-0900x600x850)</u>	900 mm	600 mm	850 mm	150 mm
<u>E25144(209-0900x600x850-R300)</u>	900 mm	600 mm	850 mm	300 mm
<u>E25144(209-0900x600x850-R450)</u>	900 mm	600 mm	850 mm	450 mm
<u>E25144(209-0900x650-R300)</u>	900 mm	650 mm	900 mm	300 mm
<u>E25144(209-0900x650-R450)</u>	900 mm	650 mm	900 mm	450 mm

03 Models and configurations

ITEM CODE	LENGTH	WIDTH	WORKING HEIGHT	REAR SPLASHBACK HEIGHT
<u>E25144(209-0900x650x1000)</u>	900 mm	650 mm	1000 mm	150 mm
<u>E25144(209-0900x650x1000-R300)</u>	900 mm	650 mm	1000 mm	300 mm
<u>E25144(209-0900x650x1000-R450)</u>	900 mm	650 mm	1000 mm	450 mm
<u>E25144(209-0900x650x850)</u>	900 mm	650 mm	850 mm	150 mm
<u>E25144(209-0900x650x850-R300)</u>	900 mm	650 mm	850 mm	300 mm
<u>E25144(209-0900x650x850-R450)</u>	900 mm	650 mm	850 mm	450 mm
<u>E25144(209-0900x700-R300)</u>	900 mm	700 mm	900 mm	300 mm
<u>E25144(209-0900x700-R450)</u>	900 mm	700 mm	900 mm	450 mm
<u>E25144(209-0900x700x1000)</u>	900 mm	700 mm	1000 mm	150 mm
<u>E25144(209-0900x700x1000-R300)</u>	900 mm	700 mm	1000 mm	300 mm
<u>E25144(209-0900x700x1000-R450)</u>	900 mm	700 mm	1000 mm	450 mm
<u>E25144(209-0900x700x850)</u>	900 mm	700 mm	850 mm	150 mm
<u>E25144(209-0900x700x850-R300)</u>	900 mm	700 mm	850 mm	300 mm
<u>E25144(209-0900x700x850-R450)</u>	900 mm	700 mm	850 mm	450 mm
<u>E25144(209-1200x0600)</u>	1200 mm	600 mm	900 mm	150 mm
<u>E25144(209-1200x0650)</u>	1200 mm	650 mm	900 mm	150 mm
<u>E25144(209-1200x0700)</u>	1200 mm	700 mm	900 mm	150 mm
<u>E25144(209-1200x600-R300)</u>	1200 mm	600 mm	900 mm	300 mm
<u>E25144(209-1200x600-R450)</u>	1200 mm	600 mm	900 mm	450 mm
<u>E25144(209-1200x600x1000)</u>	1200 mm	600 mm	1000 mm	150 mm
<u>E25144(209-1200x600x1000-R300)</u>	1200 mm	600 mm	1000 mm	300 mm
<u>E25144(209-1200x600x1000-R450)</u>	1200 mm	600 mm	1000 mm	450 mm
<u>E25144(209-1200x600x850)</u>	1200 mm	600 mm	850 mm	150 mm
<u>E25144(209-1200x600x850-R300)</u>	1200 mm	600 mm	850 mm	300 mm
<u>E25144(209-1200x600x850-R450)</u>	1200 mm	600 mm	850 mm	450 mm
<u>E25144(209-1200x650-R300)</u>	1200 mm	650 mm	900 mm	300 mm
<u>E25144(209-1200x650-R450)</u>	1200 mm	650 mm	900 mm	450 mm
<u>E25144(209-1200x650x1000)</u>	1200 mm	650 mm	1000 mm	150 mm
<u>E25144(209-1200x650x1000-R300)</u>	1200 mm	650 mm	1000 mm	300 mm
<u>E25144(209-1200x650x1000-R450)</u>	1200 mm	650 mm	1000 mm	450 mm
<u>E25144(209-1200x650x850)</u>	1200 mm	650 mm	850 mm	150 mm
<u>E25144(209-1200x650x850-R300)</u>	1200 mm	650 mm	850 mm	300 mm
<u>E25144(209-1200x650x850-R450)</u>	1200 mm	650 mm	850 mm	450 mm
<u>E25144(209-1200x700-R300)</u>	1200 mm	700 mm	900 mm	300 mm
<u>E25144(209-1200x700-R450)</u>	1200 mm	700 mm	900 mm	450 mm
<u>E25144(209-1200x700x1000)</u>	1200 mm	700 mm	1000 mm	150 mm
<u>E25144(209-1200x700x1000-R300)</u>	1200 mm	700 mm	1000 mm	300 mm
<u>E25144(209-1200x700x1000-R450)</u>	1200 mm	700 mm	1000 mm	450 mm
<u>E25144(209-1200x700x850)</u>	1200 mm	700 mm	850 mm	150 mm
<u>E25144(209-1200x700x850-R300)</u>	1200 mm	700 mm	850 mm	300 mm

03 Models and configurations

ITEM CODE	LENGTH	WIDTH	WORKING HEIGHT	REAR SPLASHBACK HEIGHT
E25144(209-1200x700x850-R450)	1200 mm	700 mm	850 mm	450 mm
E25144(209-1500x0600)	1500 mm	600 mm	900 mm	150 mm
E25144(209-1500x0650)	1500 mm	650 mm	900 mm	150 mm
E25144(209-1500x0700)	1500 mm	700 mm	900 mm	150 mm
E25144(209-1500x600-R300)	1500 mm	600 mm	900 mm	300 mm
E25144(209-1500x600-R450)	1500 mm	600 mm	900 mm	450 mm
E25144(209-1500x600x1000)	1500 mm	600 mm	1000 mm	150 mm
E25144(209-1500x600x1000-R300)	1500 mm	600 mm	1000 mm	300 mm
E25144(209-1500x600x1000-R450)	1500 mm	600 mm	1000 mm	450 mm
E25144(209-1500x600x850)	1500 mm	600 mm	850 mm	150 mm
E25144(209-1500x600x850-R300)	1500 mm	600 mm	850 mm	300 mm
E25144(209-1500x600x850-R450)	1500 mm	600 mm	850 mm	450 mm
E25144(209-1500x650-R300)	1500 mm	650 mm	900 mm	300 mm
E25144(209-1500x650-R450)	1500 mm	650 mm	900 mm	450 mm
E25144(209-1500x650x1000)	1500 mm	650 mm	1000 mm	150 mm
E25144(209-1500x650x1000-R300)	1500 mm	650 mm	1000 mm	300 mm
E25144(209-1500x650x1000-R450)	1500 mm	650 mm	1000 mm	450 mm
E25144(209-1500x650x850)	1500 mm	650 mm	850 mm	150 mm
E25144(209-1500x650x850-R300)	1500 mm	650 mm	850 mm	300 mm
E25144(209-1500x650x850-R450)	1500 mm	650 mm	850 mm	450 mm
E25144(209-1500x700-R300)	1500 mm	700 mm	900 mm	300 mm
E25144(209-1500x700-R450)	1500 mm	700 mm	900 mm	450 mm
E25144(209-1500x700x1000)	1500 mm	700 mm	1000 mm	150 mm
E25144(209-1500x700x1000-R300)	1500 mm	700 mm	1000 mm	300 mm
E25144(209-1500x700x1000-R450)	1500 mm	700 mm	1000 mm	450 mm
E25144(209-1500x700x850)	1500 mm	700 mm	850 mm	150 mm
E25144(209-1500x700x850-R300)	1500 mm	700 mm	850 mm	300 mm
E25144(209-1500x700x850-R450)	1500 mm	700 mm	850 mm	450 mm
E25144(209-1800x0600)	1800 mm	600 mm	900 mm	150 mm
E25144(209-1800x0650)	1800 mm	650 mm	900 mm	150 mm
E25144(209-1800x0700)	1800 mm	700 mm	900 mm	150 mm
E25144(209-1800x600-R300)	1800 mm	600 mm	900 mm	300 mm
E25144(209-1800x600-R450)	1800 mm	600 mm	900 mm	450 mm
E25144(209-1800x600x1000)	1800 mm	600 mm	1000 mm	150 mm
E25144(209-1800x600x1000-R300)	1800 mm	600 mm	1000 mm	300 mm
E25144(209-1800x600x1000-R450)	1800 mm	600 mm	1000 mm	450 mm
E25144(209-1800x600x850)	1800 mm	600 mm	850 mm	150 mm
E25144(209-1800x600x850-R300)	1800 mm	600 mm	850 mm	300 mm
E25144(209-1800x600x850-R450)	1800 mm	600 mm	850 mm	450 mm
E25144(209-1800x650-R300)	1800 mm	650 mm	900 mm	300 mm

03 Models and configurations

ITEM CODE	LENGTH	WIDTH	WORKING HEIGHT	REAR SPLASHBACK HEIGHT
E25144(209-1800x650-R450)	1800 mm	650 mm	900 mm	450 mm
E25144(209-1800x650x1000)	1800 mm	650 mm	1000 mm	150 mm
E25144(209-1800x650x1000-R300)	1800 mm	650 mm	1000 mm	300 mm
E25144(209-1800x650x1000-R450)	1800 mm	650 mm	1000 mm	450 mm
E25144(209-1800x650x850)	1800 mm	650 mm	850 mm	150 mm
E25144(209-1800x650x850-R300)	1800 mm	650 mm	850 mm	300 mm
E25144(209-1800x650x850-R450)	1800 mm	650 mm	850 mm	450 mm
E25144(209-1800x700-R300)	1800 mm	700 mm	900 mm	300 mm
E25144(209-1800x700-R450)	1800 mm	700 mm	900 mm	450 mm
E25144(209-1800x700x1000)	1800 mm	700 mm	1000 mm	150 mm
E25144(209-1800x700x1000-R300)	1800 mm	700 mm	1000 mm	300 mm
E25144(209-1800x700x1000-R450)	1800 mm	700 mm	1000 mm	450 mm
E25144(209-1800x700x850)	1800 mm	700 mm	850 mm	150 mm
E25144(209-1800x700x850-R300)	1800 mm	700 mm	850 mm	300 mm
E25144(209-1800x700x850-R450)	1800 mm	700 mm	850 mm	450 mm
E25144(209-2000x0600)	2000 mm	600 mm	900 mm	150 mm
E25144(209-2000x0650)	2000 mm	650 mm	900 mm	150 mm
E25144(209-2000x0700)	2000 mm	700 mm	900 mm	150 mm
E25144(209-2000x600-R300)	2000 mm	600 mm	900 mm	300 mm
E25144(209-2000x600-R450)	2000 mm	600 mm	900 mm	450 mm
E25144(209-2000x600x1000)	2000 mm	600 mm	1000 mm	150 mm
E25144(209-2000x600x1000-R300)	2000 mm	600 mm	1000 mm	300 mm
E25144(209-2000x600x1000-R450)	2000 mm	600 mm	1000 mm	450 mm
E25144(209-2000x600x850)	2000 mm	600 mm	850 mm	150 mm
E25144(209-2000x600x850-R300)	2000 mm	600 mm	850 mm	300 mm
E25144(209-2000x600x850-R450)	2000 mm	600 mm	850 mm	450 mm
E25144(209-2000x650-R300)	2000 mm	650 mm	900 mm	300 mm
E25144(209-2000x650-R450)	2000 mm	650 mm	900 mm	450 mm
E25144(209-2000x650x1000)	2000 mm	650 mm	1000 mm	150 mm
E25144(209-2000x650x1000-R300)	2000 mm	650 mm	1000 mm	300 mm
E25144(209-2000x650x1000-R450)	2000 mm	650 mm	1000 mm	450 mm
E25144(209-2000x650x850)	2000 mm	650 mm	850 mm	150 mm
E25144(209-2000x650x850-R300)	2000 mm	650 mm	850 mm	300 mm
E25144(209-2000x650x850-R450)	2000 mm	650 mm	850 mm	450 mm
E25144(209-2000x700-R300)	2000 mm	700 mm	900 mm	300 mm
E25144(209-2000x700-R450)	2000 mm	700 mm	900 mm	450 mm
E25144(209-2000x700x1000)	2000 mm	700 mm	1000 mm	150 mm
E25144(209-2000x700x1000-R300)	2000 mm	700 mm	1000 mm	300 mm
E25144(209-2000x700x1000-R450)	2000 mm	700 mm	1000 mm	450 mm
E25144(209-2000x700x850)	2000 mm	700 mm	850 mm	150 mm

03 Models and configurations

ITEM CODE	LENGTH	WIDTH	WORKING HEIGHT	REAR SPLASHBACK HEIGHT
<u>E25144(209-2000x700x850-R300)</u>	2000 mm	700 mm	850 mm	300 mm
<u>E25144(209-2000x700x850-R450)</u>	2000 mm	700 mm	850 mm	450 mm
<u>E25144(209-2400x0600)</u>	2400 mm	600 mm	900 mm	150 mm
<u>E25144(209-2400x0650)</u>	2400 mm	650 mm	900 mm	150 mm
<u>E25144(209-2400x0700)</u>	2400 mm	700 mm	900 mm	150 mm
<u>E25144(209-2400x600-R300)</u>	2400 mm	600 mm	900 mm	300 mm
<u>E25144(209-2400x600-R450)</u>	2400 mm	600 mm	900 mm	450 mm
<u>E25144(209-2400x600x1000)</u>	2400 mm	600 mm	1000 mm	150 mm
<u>E25144(209-2400x600x1000-R300)</u>	2400 mm	600 mm	1000 mm	300 mm
<u>E25144(209-2400x600x1000-R450)</u>	2400 mm	600 mm	1000 mm	450 mm
<u>E25144(209-2400x600x850)</u>	2400 mm	600 mm	850 mm	150 mm
<u>E25144(209-2400x600x850-R300)</u>	2400 mm	600 mm	850 mm	300 mm
<u>E25144(209-2400x600x850-R450)</u>	2400 mm	600 mm	850 mm	450 mm
<u>E25144(209-2400x650-R300)</u>	2400 mm	650 mm	900 mm	300 mm
<u>E25144(209-2400x650-R450)</u>	2400 mm	650 mm	900 mm	450 mm
<u>E25144(209-2400x650x1000)</u>	2400 mm	650 mm	1000 mm	150 mm
<u>E25144(209-2400x650x1000-R300)</u>	2400 mm	650 mm	1000 mm	300 mm
<u>E25144(209-2400x650x1000-R450)</u>	2400 mm	650 mm	1000 mm	450 mm
<u>E25144(209-2400x650x850)</u>	2400 mm	650 mm	850 mm	150 mm
<u>E25144(209-2400x650x850-R300)</u>	2400 mm	650 mm	850 mm	300 mm
<u>E25144(209-2400x650x850-R450)</u>	2400 mm	650 mm	850 mm	450 mm
<u>E25144(209-2400x700-R300)</u>	2400 mm	700 mm	900 mm	300 mm
<u>E25144(209-2400x700-R450)</u>	2400 mm	700 mm	900 mm	450 mm
<u>E25144(209-2400x700x1000)</u>	2400 mm	700 mm	1000 mm	150 mm
<u>E25144(209-2400x700x1000-R300)</u>	2400 mm	700 mm	1000 mm	300 mm
<u>E25144(209-2400x700x1000-R450)</u>	2400 mm	700 mm	1000 mm	450 mm
<u>E25144(209-2400x700x850)</u>	2400 mm	700 mm	850 mm	150 mm
<u>E25144(209-2400x700x850-R300)</u>	2400 mm	700 mm	850 mm	300 mm
<u>E25144(209-2400x700x850-R450)</u>	2400 mm	700 mm	850 mm	450 mm

04 Functional features**01 Grade 430 stainless steel worktop**

The worktop is Grade 430 stainless steel, 0.9 mm thick.

02 Rear splashback height choices

The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop.

03 Plain table

Supplied without an undershelf. Select a separate solid, slatted, perforated or tubular undershelf product when storage is required.

04 Working height

The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.

05 Size choices

Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available.

06 Intended working areas

An economical preparation table for catering kitchens and foodservice work areas. Eco refers to the economical product range.

05 Application information

Intended applications	Food Preparation Workstations
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.