

PRODUCT RANGE SPECIFICATION

E25144(209-P) – Grade 430 Eco Preparation Table (0.9 mm) with Rear Splashback and Perforated Undershelf

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	E25144(209-P){PSS}	Published catalogue data	15 Sep 2026

01 Product description and specification

Product description	Basterfield E25144(209-P). An economical preparation table for catering kitchens and foodservice work areas. Eco refers to the economical product range. The worktop is Grade 430 stainless steel, 0.9 mm thick. Stainless steel frame with adjustable feet. Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights. Supplied with a perforated undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. Whole-table Grade 304, Grade 430 and Grade 316 ranges are separate product alternatives, rather than material customisations. A Grade 430 undershelf does not change the specified worktop grade.
---------------------	---

Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Shall be Basterfield E25144(209-P), a Grade 430 stainless steel preparation table with rear splashback. The worktop is Grade 430 stainless steel, 0.9 mm thick. Stainless steel frame with adjustable feet. Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights. The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. Supplied with a perforated undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only.
--------------------------	--

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 430	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	The worktop is Grade 430 stainless steel, 0.9 mm thick.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Product Range	Eco	—	Product classification detail retained during the September 2026 catalogue category review.
Splashback Configuration	Rear	—	Product classification detail retained during the September 2026 catalogue category review.

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x0600-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x0600-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0500x0650-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x0650-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0500x0700-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x0700-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x600-P112AR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600-P112AR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600-P112BR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600-P112BR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600-P112R300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600-P112R450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600-P212AR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0500x600-P212AR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x600-P212BR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0500x600-P212BR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0500x600-P212R300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0500x600-P212R450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0500x600x1000-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600x1000-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0500x600x850-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0500x600x850-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x650-P112AR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650-P112AR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650-P112BR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650-P112BR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650-P112R300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650-P112R450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650-P212AR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0500x650-P212AR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x650-P212BR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0500x650-P212BR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0500x650-P212R300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0500x650-P212R450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0500x650x1000-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650x1000-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0500x650x850-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0500x650x850-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x700-P112AR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700-P112AR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700-P112BR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700-P112BR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700-P112R300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700-P112R450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700-P212AR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0500x700-P212AR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x700-P212BR300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0500x700-P212BR450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0500x700-P212R300)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0500x700-P212R450)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0500x700x1000-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700x1000-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0500x700x850-P112)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0500x700x850-P212)	Grade 430 stainless steel Eco preparation table, 500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x0600-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x0600-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x0650-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x0650-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x0700-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x0700-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0900x600-P112AR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x600-P112AR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x600-P112BR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x600-P112BR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x600-P112R300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x600-P112R450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x600-P212AR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x600-P212AR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x600-P212BR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x600-P212BR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x600-P212R300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x600-P212R450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x600x1000-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x600x1000-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x600x850-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-0900x600x850-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-0900x650-P112AR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x650-P112AR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x650-P112BR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x650-P112BR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x650-P112R300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x650-P112R450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x650-P212AR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x650-P212AR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x650-P212BR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x650-P212BR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x650-P212R300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x650-P212R450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x650x1000-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x650x1000-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x650x850-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-0900x650x850-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-0900x700-P112AR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x700-P112AR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x700-P112BR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x700-P112BR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x700-P112R300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x700-P112R450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x700-P212AR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0900x700-P212AR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0900x700-P212BR300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0900x700-P212BR450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x700-P212R300)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0900x700-P212R450)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 900 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0900x700x1000-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x700x1000-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-0900x700x850-P112)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-0900x700x850-P212)	Grade 430 stainless steel Eco preparation table, 900 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 900 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x0600-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x0600-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x0650-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x0650-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x0700-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x0700-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x600-P112AR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x600-P112AR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x600-P112BR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x600-P112BR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x600-P112R300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x600-P112R450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x600-P212AR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1200x600-P212AR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1200x600-P212BR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1200x600-P212BR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1200x600-P212R300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1200x600-P212R450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x600x1000-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x600x1000-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1200x600x850-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1200x600x850-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1200x650-P112AR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x650-P112AR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x650-P112BR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x650-P112BR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x650-P112R300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x650-P112R450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x650-P212AR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x650-P212AR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x650-P212BR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x650-P212BR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x650-P212R300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x650-P212R450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x650x1000-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x650x1000-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x650x850-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1200x650x850-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1200x700-P112AR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x700-P112AR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x700-P112BR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x700-P112BR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x700-P112R300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x700-P112R450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x700-P212AR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x700-P212AR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x700-P212BR300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x700-P212BR450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x700-P212R300)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x700-P212R450)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1200 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x700x1000-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x700x1000-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1200x700x850-P112)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1200x700x850-P212)	Grade 430 stainless steel Eco preparation table, 1200 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1200 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x0600-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x0600-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x0650-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x0650-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x0700-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x0700-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x600-P112AR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x600-P112AR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x600-P112BR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x600-P112BR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x600-P112R300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x600-P112R450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x600-P212AR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x600-P212AR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x600-P212BR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x600-P212BR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x600-P212R300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x600-P212R450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x600x1000-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x600x1000-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x600x850-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1500x600x850-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1500x650-P112AR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x650-P112AR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x650-P112BR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x650-P112BR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x650-P112R300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x650-P112R450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x650-P212AR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1500x650-P212AR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1500x650-P212BR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1500x650-P212BR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1500x650-P212R300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1500x650-P212R450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1500x650x1000-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x650x1000-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x650x850-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1500x650x850-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1500x700-P112AR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x700-P112AR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x700-P112BR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x700-P112BR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x700-P112R300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x700-P112R450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x700-P212AR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x700-P212AR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x700-P212BR300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x700-P212BR450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x700-P212R300)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x700-P212R450)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1500 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1500x700x1000-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x700x1000-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x700x850-P112)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1500x700x850-P212)	Grade 430 stainless steel Eco preparation table, 1500 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1500 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1800x0600-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x0600-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1800x0650-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x0650-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1800x0700-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x0700-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x600-P112AR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600-P112AR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600-P112BR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600-P112BR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600-P112R300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600-P112R450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600-P212AR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1800x600-P212AR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x600-P212BR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1800x600-P212BR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1800x600-P212R300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1800x600-P212R450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1800x600x1000-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600x1000-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-1800x600x850-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-1800x600x850-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x650-P112AR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650-P112AR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650-P112BR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650-P112BR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650-P112R300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650-P112R450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650-P212AR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1800x650-P212AR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x650-P212BR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1800x650-P212BR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1800x650-P212R300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1800x650-P212R450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1800x650x1000-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650x1000-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-1800x650x850-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-1800x650x850-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x700-P112AR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700-P112AR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700-P112BR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700-P112BR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700-P112R300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700-P112R450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700-P212AR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1800x700-P212AR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x700-P212BR300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1800x700-P212BR450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1800x700-P212R300)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1800x700-P212R450)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 1800 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1800x700x1000-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700x1000-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-1800x700x850-P112)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-1800x700x850-P212)	Grade 430 stainless steel Eco preparation table, 1800 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 1800 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x0600-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x0600-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x0650-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x0650-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x0700-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x0700-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2000x600-P112AR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x600-P112AR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x600-P112BR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x600-P112BR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x600-P112R300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x600-P112R450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x600-P212AR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x600-P212AR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x600-P212BR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x600-P212BR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x600-P212R300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x600-P212R450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x600x1000-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x600x1000-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x600x850-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2000x600x850-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2000x650-P112AR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x650-P112AR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x650-P112BR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x650-P112BR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x650-P112R300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x650-P112R450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x650-P212AR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x650-P212AR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x650-P212BR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x650-P212BR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x650-P212R300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x650-P212R450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x650x1000-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x650x1000-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x650x850-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2000x650x850-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2000x700-P112AR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x700-P112AR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x700-P112BR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x700-P112BR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x700-P112R300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x700-P112R450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x700-P212AR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2000x700-P212AR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2000x700-P212BR300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2000x700-P212BR450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x700-P212R300)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2000x700-P212R450)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2000 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2000x700x1000-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x700x1000-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2000x700x850-P112)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2000x700x850-P212)	Grade 430 stainless steel Eco preparation table, 2000 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2000 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x0600-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x0600-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x0650-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x0650-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x0700-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x0700-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x600-P112AR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x600-P112AR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x600-P112BR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x600-P112BR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x600-P112R300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x600-P112R450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x600-P212AR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2400x600-P212AR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2400x600-P212BR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2400x600-P212BR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2400x600-P212R300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2400x600-P212R450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x600x1000-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x600x1000-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2400x600x850-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 600 mm
E25144(209-2400x600x850-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 600 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 600 mm
E25144(209-2400x650-P112AR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x650-P112AR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x650-P112BR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x650-P112BR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x650-P112R300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x650-P112R450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x650-P212AR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x650-P212AR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x650-P212BR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x650-P212BR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x650-P212R300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x650-P212R450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x650x1000-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x650x1000-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x650x850-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 650 mm
E25144(209-2400x650x850-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 650 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 650 mm
E25144(209-2400x700-P112AR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x700-P112AR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x700-P112BR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x700-P112BR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x700-P112R300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x700-P112R450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x700-P212AR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x700-P212AR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x700-P212BR300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x700-P212BR450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x700-P212R300)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 300 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 300 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x700-P212R450)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 900 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 450 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 900 mm Length: 2400 mm Splashback Height: 450 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x700x1000-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x700x1000-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 1000 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 1000 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm
E25144(209-2400x700x850-P112)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 304 1.2 mm Width: 700 mm
E25144(209-2400x700x850-P212)	Grade 430 stainless steel Eco preparation table, 2400 mm (L) x 700 mm (W), 850 mm working height. Worktop thickness: 0.9 mm. Rear splashback: 150 mm high above worktop. Undershelf: Perforated Grade 430 1.2 mm. Stainless steel frame with adjustable feet.	Height: 850 mm Length: 2400 mm Splashback Height: 150 mm Undershelf: Perforated Grade 430 1.2 mm Width: 700 mm

04 Functional features

01	Grade 430 stainless steel worktop The worktop is Grade 430 stainless steel, 0.9 mm thick.
02	Rear splashback height choices The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop.
03	Perforated undershelf included Supplied with a perforated undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only.
04	Working height The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.
05	Size choices Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available.
06	Intended working areas An economical preparation table for catering kitchens and foodservice work areas. Eco refers to the economical product range.

05 Application information

Intended applications	Food Preparation Workstations, Preparation Tables (with Splashback)
Industries	Foodservice & Catering

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.