

PRODUCT RANGE SPECIFICATION

E25144(209-T) – Grade 430 Eco Preparation Table (0.9 mm) with Rear Splashback and Tubular Undershelf

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Product range	E25144(209-T){PSS}	Published catalogue data	5 Oct 2026

01 Product description and specification

Product description	Basterfield E25144(209-T). An economical preparation table for catering kitchens and foodservice work areas. Eco refers to the economical product range. The worktop is Grade 430 stainless steel, 0.9 mm thick. Stainless steel frame with adjustable feet. Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights. Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal. Whole-table Grade 304, Grade 430 and Grade 316 ranges are separate product alternatives, rather than material customisations. A Grade 430 undershelf does not change the specified worktop grade. Working height is measured from the floor to the worktop. Overall height includes the splashback and is calculated from the selected working and splashback heights.
---------------------	---

Short Form Specification	SPECIFICATION USE Use this description when specifying this product range. Shall be Basterfield E25144(209-T), a Grade 430 stainless steel preparation table with rear splashback. The worktop is Grade 430 stainless steel, 0.9 mm thick. Stainless steel frame with adjustable feet. Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights. The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal.
--------------------------	--

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 430	—	The primary material used in the construction of the item. Certain components may be manufactured from different materials.

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material Thickness	0.9	mm	The worktop is Grade 430 stainless steel, 0.9 mm thick.
Product Range	Eco	—	—
Splashback Configuration	Rear	—	—

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x0600-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: — x — x 1050 mm (L x W x H)
E25144(209-0500x0600-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: — x — x 1050 mm (L x W x H)
E25144(209-0500x0650-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: — x — x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x0650-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-0500x0700-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-0500x0700-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-0500x600-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x600-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x600-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x600-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0500x600-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x600-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0500x600-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0500x600-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x600-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x600-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0500x600-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-0500x600-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0500x600x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x600x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0500x600x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0500x600x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0500x650-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x650-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x650-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x650-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0500x650-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x650-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0500x650-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0500x650-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x650-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x650-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0500x650-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-0500x650-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0500x650x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x650x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0500x650x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0500x650x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0500x700-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x700-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x700-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x700-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0500x700-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x700-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0500x700-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0500x700-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0500x700-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x700-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0500x700-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-0500x700-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0500x700x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0500x700x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0500x700x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0500x700x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0900x0600-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x0600-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-0900x0650-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-0900x0650-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-0900x0700-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x0700-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-0900x600-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x600-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x600-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x600-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0900x600-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-0900x600-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0900x600-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x600-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x600-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x600-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0900x600-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x600-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0900x600x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x600x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x600x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x600x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0900x650-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x650-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x650-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x650-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0900x650-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-0900x650-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0900x650-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x650-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x650-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x650-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0900x650-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x650-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0900x650x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x650x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x650x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x650x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-0900x700-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x700-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x700-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x700-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0900x700-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-0900x700-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0900x700-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x700-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x700-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-0900x700-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-0900x700-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 900 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x700-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 900 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-0900x700x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x700x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-0900x700x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-0900x700x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 900 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 900 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1200x0600-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1200x0600-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1200x0650-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x0650-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1200x0700-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1200x0700-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1200x600-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x600-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x600-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x600-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1200x600-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x600-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1200x600-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1200x600-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x600-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x600-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1200x600-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1200x600-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1200x600x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x600x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1200x600x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1200x600x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1200x650-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x650-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x650-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x650-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1200x650-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x650-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1200x650-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1200x650-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x650-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x650-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1200x650-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1200x650-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1200x650x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x650x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1200x650x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1200x650x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1200x700-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x700-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x700-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x700-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1200x700-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x700-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1200x700-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1200x700-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1200x700-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x700-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1200x700-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1200 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1200x700-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1200 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1200x700x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1200x700x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1200x700x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1200x700x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1200 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1200 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1500x0600-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x0600-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1500x0650-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1500x0650-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1500x0700-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x0700-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1500x600-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x600-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x600-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x600-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1500x600-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1500x600-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1500x600-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x600-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x600-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x600-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1500x600-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x600-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1500x600x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x600x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x600x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x600x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1500x650-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x650-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x650-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x650-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1500x650-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1500x650-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1500x650-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x650-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x650-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x650-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1500x650-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x650-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1500x650x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x650x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x650x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x650x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1500x700-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x700-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x700-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x700-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1500x700-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1500x700-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1500x700-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x700-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x700-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1500x700-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1500x700-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1500 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x700-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1500 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1500x700x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x700x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1500x700x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1500x700x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1500 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1500 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1800x0600-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1800x0600-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1800x0650-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x0650-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1800x0700-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1800x0700-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-1800x600-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x600-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x600-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x600-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1800x600-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x600-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1800x600-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1800x600-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x600-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x600-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1800x600-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1800x600-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1800x600x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x600x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1800x600x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1800x600x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1800x650-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x650-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x650-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x650-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1800x650-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x650-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1800x650-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1800x650-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x650-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x650-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1800x650-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1800x650-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1800x650x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x650x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1800x650x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1800x650x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1800x700-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x700-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x700-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x700-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1800x700-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x700-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1800x700-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1800x700-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-1800x700-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x700-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-1800x700-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 1800 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-1800x700-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 1800 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-1800x700x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-1800x700x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-1800x700x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-1800x700x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 1800 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 1800 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2000x0600-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x0600-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2000x0650-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2000x0650-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2000x0700-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x0700-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2000x600-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x600-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x600-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x600-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2000x600-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-2000x600-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2000x600-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x600-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x600-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x600-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2000x600-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x600-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2000x600x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x600x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x600x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x600x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2000x650-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x650-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x650-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x650-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2000x650-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-2000x650-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2000x650-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x650-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x650-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x650-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2000x650-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x650-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2000x650x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x650x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x650x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x650x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2000x700-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x700-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x700-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x700-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2000x700-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-2000x700-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2000x700-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x700-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x700-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2000x700-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2000x700-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2000 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x700-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2000 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2000x700x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x700x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2000x700x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2000x700x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2000 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2000 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2400x0600-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2400x0600-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2400x0650-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x0650-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2400x0700-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2400x0700-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1050 mm (L x W x H)
E25144(209-2400x600-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x600-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x600-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x600-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2400x600-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x600-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2400x600-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2400x600-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x600-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x600-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2400x600-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-2400x600-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2400x600x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x600x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2400x600x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2400x600x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 600 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 600 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2400x650-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x650-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x650-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x650-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2400x650-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x650-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2400x650-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2400x650-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x650-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x650-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2400x650-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-2400x650-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2400x650x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x650x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2400x650x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2400x650x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 650 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 650 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2400x700-T112AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x700-T112AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x700-T112BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x700-T112BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2400x700-T112R300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x700-T112R450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2400x700-T212AR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 300 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2400x700-T212AR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 450 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1300 mm (L x W x H)
E25144(209-2400x700-T212BR300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1300 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x700-T212BR450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 450 mm Splashback (1450 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1450 mm (L x W x H)
E25144(209-2400x700-T212R300)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 300 mm Splashback (1200 mm Overall).	Length: 2400 mm Splashback Height: 300 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1200 mm (L x W x H)
E25144(209-2400x700-T212R450)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 900 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 450 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 450 mm Splashback (1350 mm Overall).	Length: 2400 mm Splashback Height: 450 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 900 mm Overall dimensions: – x – x 1350 mm (L x W x H)
E25144(209-2400x700x1000-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)

03 Models and configurations

MODEL	DESCRIPTION	PUBLISHED CONFIGURATION
E25144(209-2400x700x1000-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 1000 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 1000 mm Working Height, with a 150 mm Splashback (1150 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 1000 mm Overall dimensions: – x – x 1150 mm (L x W x H)
E25144(209-2400x700x850-T112)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 304 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 304 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)
E25144(209-2400x700x850-T212)	Grade 430 Stainless Steel Eco Preparation Table, 2400 mm (L) x 700 mm (W), 850 mm Working Height. Worktop Thickness: 0.9 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 850 mm Working Height, with a 150 mm Splashback (1000 mm Overall).	Length: 2400 mm Splashback Height: 150 mm Undershelf: Tubular Grade 430 1.2 mm (open section) Width: 700 mm Working Height: 850 mm Overall dimensions: – x – x 1000 mm (L x W x H)

04 Functional features

01 Grade 430 stainless steel worktop

The worktop is Grade 430 stainless steel, 0.9 mm thick.

02 Rear splashback height choices

The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop.

03 Tubular undershelf included

Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal.

04 Working height

The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.

- 05

Size choices

Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available.
- 06

Intended working areas

An economical preparation table for catering kitchens and foodservice work areas. Eco refers to the economical product range.

05

Application information

Intended applications	Food Preparation Workstations
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06

Supply and support

Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED

Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.