MODEL SPECIFICATION

# E25144(212-0500x600-L112BR300) – Table, Slatted Shelf 500 mmx600 mm SB300 mm

| DOCUMENT SCOPE | DOCUMENT REFERENCE | GENERATED ON |
|---|---|---|
| Model | E25144(212-0500x600-L112BR300) {PSS} | 15 Nov 2026 |

## 01 Model specification

Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 1000 mm Working Height. Worktop Thickness: 1.2 mm. Rear Splashback: 300 mm High Above Worktop. Undershelf: Slatted Grade 304 1.2 mm. Stainless Steel Frame with Adjustable Feet.

Height Specification: 1000 mm Working Height, with a 300 mm Splashback (1300 mm Overall).

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Working Height** | 1000 | mm | The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights. |
| **Splashback Height** | 300 | mm | The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. |
| **Overall height** | 1300 | mm | Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height. |
| **Material Thickness** | 1.2 | mm | The worktop is Grade 430 stainless steel, 1.2 mm thick. Advanced customisation offers 1.5 mm or 2 mm worktops. |


121 Koornhof Road, Meadowdale, Germiston, South Africa, 1614 · hello@basterfield.co.za · basterfield.co.za · +27 87 095 5357

## 02 Technical specifications

| PARAMETER | VALUE | UNIT | TECHNICAL NOTE |
|---|---|---|---|
| **Undershelf** | Slatted Grade 304 1.2 mm | — | Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration. |
| **Length** | 500 | mm | The length of the item typically as measured from left to right. |
| **Width** | 600 | mm | The width of the item typically as measured from front to back. |
| **Material** | Stainless Steel Grade 430 | — | The primary material used in the construction of the item. Certain components may be manufactured from different materials. |

## 03 Dimensions and mass

| PARAMETER | VALUE | UNIT |
|---|---|---|
| **Overall height** | 1300 | mm |

## 04 Model and supply data

| | |
|---|---|
| **Parent product** | E25144(212) — Grade 430 Eco Preparation Table (1.2 mm) with Rear Splashback |
| **Typical lead time** | 10–15 working days |
| **Warranty** | 24 months |

## 05 Frequently asked questions

**What is the standard configuration?**

The standard worktop is 1.2 mm thick and the standard working height is 900 mm. The worktop is Grade 430 stainless steel. Stainless steel frame with adjustable feet.

**Which undershelf options are available?**

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

**Which sizes are available?**

Lengths: 500, 900, 1200, 1500, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Available combinations vary by undershelf and worktop specification; select the required options in the configurator.

**Which advanced options are available?**

Advanced customisation offers 1.5 mm or 2 mm worktops and 850 mm or 1000 mm working heights. Rear splashback heights of 300 mm and 450 mm are also available.

**How is the height measured?**

The rear splashback is 150 mm high as standard, with 300 mm and 450 mm advanced options. Working height is measured from the floor to the worktop; overall height includes the splashback.

**Can I choose another stainless steel grade?**

The worktop and table range remain Grade 430; the selected undershelf specification is shown separately. Whole-table Grade 304, Grade 430 and Grade 316 tables remain separate product alternatives. Grade 316 tables are outside the Eco range.

E&OE. Specifications are subject to change without notice.