

MODEL SPECIFICATION

**E25144(212-0500x0600-T212) – Grade 430 Stainless Steel Eco Preparation Table, 500 mm (L) x 600 mm (W), 900 mm Working Height. Worktop Thickness: 1.2 mm. Rear Splashback: 150 mm High Above Worktop. Undershelf: Tubular Grade 430 1.2 mm (Open Section). Stainless Steel Frame with Adjustable Feet. Tubular Undershelf Uses Formed Open-Section Sheet Metal. Height Specification: 900 mm Working Height, with a 150 mm Splashback (1050 mm Overall).**

|                |                                 |                          |              |
|----------------|---------------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE              | DATA STATUS              | GENERATED ON |
| Model          | E25144(212-0500x0600-T212){PSS} | Published catalogue data | 5 Oct 2026   |

01 Technical specifications

| PARAMETER          | VALUE | UNIT | TECHNICAL NOTE                                                                                                                                                                                  |
|--------------------|-------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Working Height     | 900   | mm   | The standard working height is 900 mm, measured from the floor to the worktop. Advanced customisation offers 850 mm or 1000 mm working heights.                                                 |
| Splashback Height  | 150   | mm   | The rear splashback is 150 mm high as standard. Advanced customisation offers 300 mm or 450 mm splashbacks, measured above the worktop. The splashback runs along the rear edge of the worktop. |
| Overall height     | 1050  | mm   | Overall vertical envelope, including the splashback where fitted. For tables and sinks, this is distinct from working height.                                                                   |
| Material Thickness | 1.2   | mm   | The worktop is Grade 430 stainless steel, 1.2 mm thick. Advanced customisation offers 1.5 mm or 2 mm worktops.                                                                                  |
| Length             | 500   | mm   | The length of the item typically as measured from left to right.                                                                                                                                |
| Width              | 600   | mm   | The width of the item typically as measured from front to back.                                                                                                                                 |

01 Technical specifications

| PARAMETER  | VALUE                                   | UNIT | TECHNICAL NOTE                                                                                                                                      |
|------------|-----------------------------------------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Undershelf | Tubular Grade 430 1.2 mm (open section) | —    | Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal. |
| Material   | Stainless Steel Grade 430               | —    | The primary material used in the construction of the item. Certain components may be manufactured from different materials.                         |

02 Dimensions and mass

| PARAMETER      | VALUE | UNIT |
|----------------|-------|------|
| Overall height | 1050  | mm   |

03 Model and supply data

|                   |                                                                                                      |
|-------------------|------------------------------------------------------------------------------------------------------|
| Parent product    | E25144(212-T) – Grade 430 Eco Preparation Table (1.2 mm) with Rear Splashback and Tubular Undershelf |
| Typical lead time | 10–15 working days                                                                                   |
| Warranty          | 12 months                                                                                            |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.