PRODUCT RANGE SPECIFICATION

E25145(109) – Grade 304 Eco Preparation Table (0.9 mm)



PRODUCT IMAGE · Basterfield preparation table layout illustration, without an undershelf and without a splashback. Dimensions, material grade, worktop thickness and optional undershelf depend on the selected model.

ⓘ Product image is representative of the range and may not reflect the actual item.

DOCUMENT SCOPE	DOCUMENT REFERENCE	GENERATED ON
Product range	**E25145(109){PSS}**	**14 Nov 2026**

Detailed item specifications

View available models and configuration options on the product page. Select a model to download its detailed specification sheet with dimensions, technical specifications and drawings. Scan the QR code or follow the link below.

https://basterfield.co.za/products/e25145109-grade-304-eco-preparation-table-09-mm#specifications

01 Product description and specification

Product description

Grade 304 table with a 0.9 mm standard worktop, adjustable feet and a choice of no undershelf, solid, slatted, perforated or tubular undershelf.

Short Form Specification

SPECIFICATION USE
Use this description when specifying this product range.

Basterfield E25145(109). The standard worktop is 0.9 mm thick and the standard working height is 900 mm. The worktop is Grade 304 stainless steel. Stainless steel frame with adjustable feet. This table has no splashback. Working height is measured from the floor to the worktop and equals overall height. Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration. Confirm the selected configuration's dimensions, undershelf material, thickness and mass on its item specification sheet.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	0.9	mm	The worktop is Grade 304 stainless steel, 0.9 mm thick. Choose a separate table range when a thicker worktop is required.

02 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Product Range	Eco	–	–
Splashback Configuration	None	–	–

03 Configuration options

Length	500 mm; 900 mm; 1200 mm; 1500 mm; 1700 mm; 1800 mm; 2000 mm; 2400 mm
Width	600 mm; 650 mm; 700 mm
Undershelf specification	No undershelf; Perforated Grade 304 1.2 mm; Perforated Grade 430 1.2 mm; Slatted Grade 304 1.2 mm; Slatted Grade 430 1.2 mm; Solid Grade 304 0.9 mm; Solid Grade 304 1.2 mm; Solid Grade 430 0.9 mm; + 3 more

Options vary by model; not every combination is available. Use the product page to select a model.

04 Functional features

01 **Grade 304 worktop**
The worktop is Grade 304 stainless steel, 0.9 mm thick. Choose a separate table range when a thicker worktop is required.

02 **Economical catering range**
An economical preparation table for catering kitchens and foodservice work areas, with a stainless steel frame and adjustable feet. Eco refers to the economical product range.

03 **Adjustable feet**
Adjustable feet allow levelling at the selected working height.

04 **Choice of undershelf configuration**
Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

05 **Size and height choices**
Lengths of 500, 900, 1200, 1500, 1800, 2000 or 2400 mm, and widths of 600, 650 or 700 mm are available. The standard working height is 900 mm. Advanced customisation offers 850 mm or 1000 mm working heights.

05 Application information

Intended applications	Food Preparation Workstations
Industries	Hotels & Lodges, Institutional & Contract Catering, Restaurants & Cafés

06 Supply and support

Typical lead time	10–15 working days
Warranty	24 months

07 Frequently asked questions

What is the standard configuration?

The standard worktop is 0.9 mm thick and the standard working height is 900 mm. The worktop is Grade 304 stainless steel. Stainless steel frame with adjustable feet.

Which undershelf options are available?

Choose no undershelf, or a solid, slatted, perforated or tubular undershelf. Solid undershelves are available in Grade 304 or Grade 430 stainless steel, 0.9 mm or 1.2 mm thick. Slatted, perforated and tubular undershelves are available in Grade 304 or Grade 430, 1.2 mm thick. The tubular design uses formed open-section sheet metal. Available sizes depend on the selected configuration.

Which sizes are available?

Lengths: 500, 900, 1200, 1500, 1700, 1800, 2000, 2400 mm. Widths: 600, 650, 700 mm. Available combinations vary by undershelf and worktop specification; select the required options in the configurator.

Which advanced options are available?

Advanced customisation offers 850 mm or 1000 mm working heights.

How is the height measured?

This table has no splashback. Working height is measured from the floor to the worktop and equals overall height.

Can I choose another stainless steel grade?

The worktop and table range remain Grade 304; the selected undershelf specification is shown separately. Whole-table Grade 304, Grade 430 and Grade 316 tables remain separate product alternatives. Grade 316 tables are outside the Eco range.

E&OE. Specifications are subject to change without notice.