

MODEL SPECIFICATION

E25145(112-0500x0650-P112) – Grade 304 stainless steel preparation table, 500 mm (L) x 650 mm (W) x 900 mm (H). Worktop thickness: 1.2 mm. Undershelf: Perforated Grade 304 1.2 mm. Stainless steel frame and legs with adjustable stainless steel feet.

DOCUMENT SCOPE	DOCUMENT REFERENCE	DATA STATUS	GENERATED ON
Model	E25145(112-0500x0650-P112){PSS}	Published catalogue data	15 Sep 2026

01 Technical specifications

PARAMETER	VALUE	UNIT	TECHNICAL NOTE
Material	Stainless Steel Grade 304	–	The primary material used in the construction of the item. Certain components may be manufactured from different materials.
Material Thickness	1.2	mm	Grade 304 worktop: 1.2 mm standard; 1.5 mm or 2 mm through advanced customisation.
Length	500	mm	The length of the item typically as measured from left to right.
Height	900	mm	900 mm standard; 850 mm or 1000 mm through advanced customisation.
Width	650	mm	The width of the item typically as measured from front to back.
Undershelf	Perforated Grade 304 1.2 mm	–	Supplied with a perforated undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only.

02 Model and supply data

Parent product	E25145(112-P) – Stainless Steel Heavy Duty Preparation Table with Perforated Undershelf
Typical lead time	10–15 working days
Warranty	12 months

VERIFICATION REQUIRED Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.