

MODEL SPECIFICATION

**E25145(112-0500x0650-T212) – Grade 304 stainless steel preparation table, 500 mm (L) x 650 mm (W) x 900 mm (H). Worktop thickness: 1.2 mm. Undershelf: Tubular Grade 430 1.2 mm (open section). Stainless steel frame and legs with adjustable stainless steel feet. Tubular undershelf uses formed open-section sheet metal.**

|                |                                 |                          |              |
|----------------|---------------------------------|--------------------------|--------------|
| DOCUMENT SCOPE | DOCUMENT REFERENCE              | DATA STATUS              | GENERATED ON |
| Model          | E25145(112-0500x0650-T212){PSS} | Published catalogue data | 15 Sep 2026  |

01 Technical specifications

| PARAMETER          | VALUE                                   | UNIT | TECHNICAL NOTE                                                                                                                                      |
|--------------------|-----------------------------------------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Material           | Stainless Steel Grade 304               | –    | The primary material used in the construction of the item. Certain components may be manufactured from different materials.                         |
| Material Thickness | 1.2                                     | mm   | Grade 304 worktop: 1.2 mm standard; 1.5 mm or 2 mm through advanced customisation.                                                                  |
| Length             | 500                                     | mm   | The length of the item typically as measured from left to right.                                                                                    |
| Height             | 900                                     | mm   | 900 mm standard; 850 mm or 1000 mm through advanced customisation.                                                                                  |
| Width              | 650                                     | mm   | The width of the item typically as measured from front to back.                                                                                     |
| Undershelf         | Tubular Grade 430 1.2 mm (open section) | –    | Supplied with a tubular undershelf in Grade 304 or Grade 430 stainless steel, 1.2 mm only. The tubular design uses formed open-section sheet metal. |

02 Model and supply data

|                   |                                                                                      |
|-------------------|--------------------------------------------------------------------------------------|
| Parent product    | E25145(112-T) – Stainless Steel Heavy Duty Preparation Table with Tubular Undershelf |
| Typical lead time | 10–15 working days                                                                   |
| Warranty          | 12 months                                                                            |

**VERIFICATION REQUIRED** Published values are provided for initial specification. Confirm the selected model, critical dimensions, site services, clearances, and the latest document revision with Basterfield before procurement, manufacture, or installation. E&OE. Specifications are subject to change without notice.